Specification document of S-5813A, S-5814A

Component manufacturer	ABLIC
Model number	S-5813A, S-5814A
Datasheets	S-5813A/5814A Series TEMPERATURE SENSOR IC (ablic.com)
Specification Ver	01.00.00 Sep 30,2022 New release
Documentation provided	Rui Long Lab Inc. https://rui-long-lab.com/

1. Component datasheet

Accuracy against temperature	S-5813A ±5.0° C (-30 ° C to +100° C) S-5814A ±2.5° C (-30 ° C to +100° C)
Range of power supply voltage(Vdd)	2.9 to 10.0[V]
Output voltage (Vout)	Linear -11.04 [mV/° C] Typ. (-30° C to 100° C) Vdd = 5.0 [V] -30 [° C] 2.582 [V] Typ. 30 [° C] 1.940 [V] Typ. 100 [° C] 1.145 [V] Typ.
Vdd vs Vout	Non-link (ΔVout 0.006 to 0.007 [V])

Ta[° C]	Vdd[V]	Vout[V]
-40	3.00	2.677
	10.00	2.683
30	2.48	1.934
	10.00	1.940
100	2.48	1.142
	10.00	1.149

2. Component Software IF specification

The software interface specifications based on the S-5813A/S-5814A component specifications are as follows.
The voltage value-to-physical value conversion equation is a linear conversion equation as shown in the equation below.

ADC value to voltage value conversion formula

$$vi = (ai \times iADC\_vdd) / 2^{iADC\_bit} \quad [V]$$

Voltage value to physical value conversion formula

$$y = (vi - iS5813A\_xoff) / iS5813A\_gain + iS5813A\_yoff \quad [℃]$$

$$iS5813A\_min \leqq y \leqq iS5813A\_max$$

ai	A/D conversion value
vi	Sensor output voltage value [V]
iADC_vdd	Sensor supply voltage value [V]
iADC_bit	A/D conversion bit length
y	Temperature value [℃]

```
#define iS5813A_xoff        1.940F          // X offset [V]
#define iS5813A_yoff        30.0F           // Y offset [℃]
#define iS5813A_gain        -0.01104F       // Gain [V/℃]
#define iS5813A_max         100.0F          // Temperature Max [℃]
#define iS5813A_min         -30.0F          // Temperature Min [℃]
```


Datasheet : OSS-EC
2.8
2.6
2.4
2.2
2
1.8
1.6
1.4
1.2
1
2.582
2.602
2.475
2.492
2.368
2.382
2.261
2.271
2.154
2.161
2.047
2.05
1.94
1.94
1.826
1.83
1.712
1.719
1.598
1.609
1.484
1.498
1.37
1.388
1.256
1.278
1.145
1.167
-30
-20
-10
0
10
20
30
40
50
60
70
80
90
100
Vout(Datasheet)
Vout(OSS-EC)

3. File Structure and Definitions

S5813A.h

```
#include "user_define.h"

// Components number
#define iS5813A              104U                    // ABLIC S-5813A, S-5814A

// S-5813A,S-5814A System Parts definitions
#define iS5813A_xoff         1.940F                  // X offset [V]
#define iS5813A_yoff         30.0F                   // Y offset [℃]
#define iS5813A_gain         -0.01104F               // Gain [V/℃]
#define iS5813A_max          100.0F                  // Temperature Max [℃]
#define iS5813A_min          -30.0F                  // Temperature Min [℃]

extern const tbl_adc_t tbl_S5813A;
```

S5813A.cpp

```
#include        "S5813A.h"
#if     iS5813A_ma == iSMA                          // Simple moving average filter
static float32 S5813A_sma_buf[iS5813A_SMA_num];
static const sma_f32_t S5813A_Phy_SMA =
{
        iInitial ,                                  // Initial state
        iS5813A_SMA_num ,                           // Simple moving average number & buf size
        0U ,                                        // buffer position
        0.0F ,                                      // sum
        &S5813A_sma_buf[0]                          // buffer
};
#elif   iS5813A_ma == iEMA                          // Exponential moving average filter
static const ema_f32_t S5813A_Phy_EMA =
{
        iInitial ,                                  // Initial state
        0.0F ,                                      // Xn-1
        iS5813A_EMA_K                               // Exponential smoothing factor
};
#elif   iS5813A_ma == iWMA                          // Weighted moving average filter
static float32 S5813A_wma_buf[iS5813A_WMA_num];
static const wma_f32_t S5813A_Phy_WMA =
{
        iInitial ,                                  // Initial state
        iS5813A_WMA_num ,                           // Weighted moving average number & buf size
        0U ,                                        // buffer poition
        iS5813A_WMA_num * (iS5813A_WMA_num + 1)/2 , // kn sum
        &S5813A_wma_buf[0]                          // Xn buffer
};
#else                                               // Non-moving average filter
#endif

#define iDummy_adr      0xffffffff                  // Dummy address

const tbl_adc_t tbl_S5813A =
{
```

```
        iS5813A             ,
        iS5813A_pin         ,
        iS5813A_xoff        ,
        iS5813A_yoff        ,
        iS5813A_gain        ,
        iS5813A_max         ,
        iS5813A_min         ,
        iS5813A_ma          ,

#if     iS5813A_ma == iSMA                  // Simple moving average filter
        &S5813A_Phy_SMA     ,
        (ema_f32_t*)iDummy_adr  ,
        (wma_f32_t*)iDummy_adr
#elif   iS5813A_ma == iEMA                  // Exponential moving average filter
        (sma_f32_t*)iDummy_adr  ,
        &S5813A_Phy_EMA     ,
        (wma_f32_t*)iDummy_adr
#elif   iS5813A_ma == iWMA                  // Weighted moving average filter
        (sma_f32_t*)iDummy_adr  ,
        (ema_f32_t*)iDummy_adr  ,
        &S5813A_Phy_WMA
#else                                         // Non-moving average filter
        (sma_f32_t*)iDummy_adr  ,
        (ema_f32_t*)iDummy_adr  ,
        (wma_f32_t*)iDummy_adr
#endif

};
```