

Specification document of AD22100A

Component manufacturer	Analog Devices		
Model number	AD22100A		
Datasheets	AD22100 (REV. D) (analog.com)		
Specification Ver	01.00.00	Oct 03,2022	New release
Documentation provided	Rui Long Lab Inc. https://rui-long-lab.com/		

1. Component datasheet	2
2. Component Software IF specification	3
3. File Structure and Definitions	5

License

Open Source Software for Embedded Components ("OSS-EC") is open source software files and related documentation files for component products used in computer systems and other applications. OSS-EC is provided to those who accept the OSS-EC Terms of Use for the OSS-EC site; see https://oss-ec.com/license_agreement/ for the OSS-EC Terms of Use. By downloading the OSS-EC from the OSS-EC site or obtaining the OSS-EC by any means, you accept the Terms of Use. Please read and accept the Terms of Use before using the OSS-EC. If you do not agree to the Terms of Use, please do not use the OSS-EC. We reserve the right to change these Terms of Use at any time and for any reason. We strongly recommend that you review the Terms of Use periodically.

1. Component datasheet

Temperature accuracy	$\pm 2.0^\circ \text{ C}$ (-40° C to $+85^\circ \text{ C}$)
Range of power supply voltage (Vdd)	4.0 to 6.5[V]
Output voltage (Vout)	Linear $22.5 \times \text{Vdd}/5 \text{ [mV/}^\circ \text{ C]}$ Typ. $\text{Vdd} = 5.0 \text{ [V]}$ $-40 [^\circ \text{ C}] \quad 0.475[\text{V}] \text{ Typ.}$ $85 [^\circ \text{ C}] \quad 3.288 [\text{V}] \text{ Typ.}$
Calculation	$\text{Vout} = (\text{Vdd}/5 \text{ V}) \times (1.375 \text{ V} + 22.5 \text{ mV/}^\circ \text{ C} \times \text{Ta})$ $\text{Ta} = (\text{Vout} / (\text{Vdd}/5\text{V})) - 1.375\text{V} / 22.5 \text{ mV/}^\circ \text{ C}$

2. Component Software IF specification

The software interface specifications based on the AD22100A component specifications are as follows.

The voltage value-to-physical value conversion equation is a linear conversion equation as shown in the equation below.

ADC value to voltage value conversion formula

$$vi = (ai \times iADC_vdd) / 2^{iADC_bit} [V]$$


Voltage value to physical value conversion formula

$$y = (vi - iAD22100A_xoff) / iAD22100A_gain + iAD22100A_yoff [^{\circ}C]$$

$$iAD22100A_{min} \leqq y \leqq iAD22100A_{max}$$

ai	A/D conversion value
vi	Sensor output voltage value [V]
iADC_vdd	Sensor supply voltage value [V]
iADC_bit	A/D conversion bit length
y	Temperature value [^{\circ}C]
#define iAD22100A_xoff	<u>(1.375F*(iADC_vdd/5.0))</u> // X offset [V]
#define iAD22100A_yoff	<u>0.0F</u> // Y offset [^{\circ}C]
#define iAD22100A_gain	<u>(0.0225F*(iADC_vdd/5.0))</u> // Gain [V/^{\circ}C]
#define iAD22100A_max	<u>85.0F</u> // Temperature Max [^{\circ}C]
#define iAD22100A_min	<u>-40.0F</u> // Temperature Min [^{\circ}C]

Datasheet : OSS-EC



3. File Structure and Definitions

AD22100A.h

```
#include "user_define.h"

// Components number
#define iAD22100A          106U           // Analog devices AD22100A

// AD22100A System Parts definitions
#define iAD22100A_xoff      (1.375F*(iADC_vdd/5.0)) // X offset [V]
#define iAD22100A_yoff      0.0F           // Y offset [°C]
#define iAD22100A_gain      (0.0225F*(iADC_vdd/5.0)) // Gain [V/°C]
#define iAD22100A_max       85.0F          // Temperature Max [°C]
#define iAD22100A_min       -40.0F         // Temperature Min [°C]

extern const tbl_adc_t tbl_AD22100A;
```

AD22100A.cpp

```

#include      "AD22100A.h"
#if      iAD22100A_ma == iSMA           // Simple moving average filter
static float32 AD22100A_sma_buf[iAD22100A_SMA_num];
static const sma_f32_t AD22100A_PhysMA =
{
    iInitial ,                                // Initial state
    iAD22100A_SMA_num ,                      // Simple moving average number & buf
    size
    0U ,                                       // buffer position
    0.0F ,                                      // sum
    &AD22100A_sma_buf[0]                      // buffer
};

#elif    iAD22100A_ma == iEMA           // Exponential moving average filter
static const ema_f32_t AD22100A_PhysEMA =
{
    iInitial ,                                // Initial state
    0.0F ,                                     // Xn-1
    iAD22100A_EMA_K                          // Exponential smoothing factor
};

#elif    iAD22100A_ma == iWMA           // Weighted moving average filter
static float32 AD22100A_wma_buf[iAD22100A_WMA_num];
static const wma_f32_t AD22100A_PhysWMA =
{
    iInitial ,                                // Initial state
    iAD22100A_WMA_num ,                      // Weighted moving average number & buf size
    0U ,                                       // buffer poition
    iAD22100A_WMA_num * (iAD22100A_WMA_num + 1)/2 , // kn sum
    &AD22100A_wma_buf[0]                      // Xn buffer
};

#else                           // Non-moving average filter
#endif

#define iDummy_adr      0xffffffff          // Dummy address

const tbl_adc_ttbl_AD22100A =

```

```

{

  iAD22100A      ,
  iAD22100A_pin   ,
  iAD22100A_xoff  ,
  iAD22100A_yoff  ,
  iAD22100A_gain  ,
  iAD22100A_max   ,
  iAD22100A_min   ,
  iAD22100A_ma    ,

#if      iAD22100A_ma == iSMA           // Simple moving average filter
&AD22100A_PhysMA      ,
(ema_f32_t*) iDummy_adr  ,
(wma_f32_t*) iDummy_adr

#elif    iAD22100A_ma == iEMA           // Exponential moving average filter
(sma_f32_t*) iDummy_adr  ,
&AD22100A_PhysEMA      ,
(wma_f32_t*) iDummy_adr

#elif    iAD22100A_ma == iWMA           // Weighted moving average filter
(sma_f32_t*) iDummy_adr  ,
(ema_f32_t*) iDummy_adr  ,
(wma_f32_t*) iDummy_adr
&AD22100A_PhysWMA

#else                           // Non-moving average filter
(sma_f32_t*) iDummy_adr  ,
(ema_f32_t*) iDummy_adr  ,
(wma_f32_t*) iDummy_adr

#endif

} ;

```