



Specification document of AD22100K

Component manufacturer	Analog Devices		
Model number	AD22100K		
Datasheets	AD22100 (REV. D) (analog.com)		
Specification Ver	01.00.00	Oct 03,2022	New release
Documentation provided	Rui Long Lab Inc. https://rui-long-lab.com/		

1. Component datasheet	2
2. Component Software IF specification	3
3. File Structure and Definitions	5

License

Open Source Software for Embedded Components ("OSS-EC") is open source software files and related documentation files for component products used in computer systems and other applications. OSS-EC is provided to those who accept the OSS-EC Terms of Use for the OSS-EC site; see https://oss-ec.com/license_agreement/ for the OSS-EC Terms of Use. By downloading the OSS-EC from the OSS-EC site or obtaining the OSS-EC by any means, you accept the Terms of Use. Please read and accept the Terms of Use before using the OSS-EC. If you do not agree to the Terms of Use, please do not use the OSS-EC. We reserve the right to change these Terms of Use at any time and for any reason. We strongly recommend that you review the Terms of Use periodically.

1. Component datasheet

Temperature accuracy	$\pm 0.75^{\circ}\text{C}$ (0°C to $+100^{\circ}\text{C}$)
Range of power supply voltage (Vdd)	4.0 to 6.5[V]
Output voltage (Vout)	Linear $22.5 \times \text{Vdd}/5$ [mV/ $^{\circ}\text{C}$] Typ. Vdd = 5.0 [V] 0 [$^{\circ}\text{C}$] 1.375[V] Typ. 100 [$^{\circ}\text{C}$] 3.625 [V] Typ.
Calculation	$\text{Vout} = (\text{Vdd}/5\text{ V}) \times (1.375\text{ V} + 22.5\text{ mV}/^{\circ}\text{C} \times \text{Ta})$ $\text{Ta} = (\text{Vout} / (\text{Vdd}/5\text{V})) - 1.375\text{V}) / 22.5\text{ mV}/^{\circ}\text{C}$

2. Component Software IF specification

The software interface specifications based on the AD22100K component specifications are as follows.

The voltage value-to-physical value conversion equation is a linear conversion equation as shown in the equation below.

ADC value to voltage value conversion formula


$$v_i = (a_i \times i_{ADC_vdd}) / 2^{i_{ADC_bit}} \quad [V]$$

Voltage value to physical value conversion formula

$$y = (v_i - i_{AD22100K_xoff}) / i_{AD22100K_gain} + i_{AD22100K_yoff} \quad [^{\circ}C]$$

$$i_{AD22100K_min} \leq y \leq i_{AD22100K_max}$$

a_i	A/D conversion value
v_i	Sensor output voltage value [V]
i_{ADC_vdd}	Sensor supply voltage value [V]
i_{ADC_bit}	A/D conversion bit length
y	Temperature value [$^{\circ}C$]
#define $i_{AD22100K_xoff}$	<u>$(1.375F * (i_{ADC_vdd} / 5.0))$</u> // X offset [V]
#define $i_{AD22100K_yoff}$	<u>0.0F</u> // Y offset [$^{\circ}C$]
#define $i_{AD22100K_gain}$	<u>$(0.0225F * (i_{ADC_vdd} / 5.0))$</u> // Gain [V/ $^{\circ}C$]
#define $i_{AD22100K_max}$	<u>100.0F</u> // Temperature Max [$^{\circ}C$]
#define $i_{AD22100K_min}$	<u>0.0F</u> // Temperature Min [$^{\circ}C$]



3. File Structure and Definitions

AD22100K.h

```
#include "user_define.h"

// Components number
#define iAD22100K          107U          // Analog devices AD22100K

// AD22100K System Parts definitions
#define iAD22100K_xoff    (1.375F*(iADC_vdd/5.0)) // X offset [V]
#define iAD22100K_yoff    0.0F                // Y offset [°C]
#define iAD22100K_gain    (0.0225F*(iADC_vdd/5.0)) // Gain [V/°C]
#define iAD22100K_max     100.0F              // Temperature Max [°C]
#define iAD22100K_min     0.0F                // Temperature Min [°C]

extern const tbl_adc_t tbl_AD22100K;
```

AD22100K.cpp

```
#include      "AD22100K.h"

#if      iAD22100K_ma == iSMA                // Simple moving average filter
static float32 AD22100K_sma_buf[iAD22100K_SMA_num];
static const sma_f32_t AD22100K_Phy_SMA =
{
    iInitial ,                                // Initial state
    iAD22100K_SMA_num ,                      // Simple moving average number & buf
size
    OU ,                                     // buffer position
    0.0F ,                                    // sum
    &AD22100K_sma_buf[0]                    // buffer
};

#elif      iAD22100K_ma == iEMA                // Exponential moving average filter
static const ema_f32_t AD22100K_Phy_EMA =
{
    iInitial ,                                // Initial state
    0.0F ,                                    // Xn-1
    iAD22100K_EMA_K                          // Exponential smoothing factor
};

#elif      iAD22100K_ma == iWMA                // Weighted moving average filter
static float32 AD22100K_wma_buf[iAD22100K_WMA_num];
static const wma_f32_t AD22100K_Phy_WMA =
{
    iInitial ,                                // Initial state
    iAD22100K_WMA_num ,                      // Weighted moving average number & buf size
    OU ,                                     // buffer poition
    iAD22100K_WMA_num * (iAD22100K_WMA_num + 1)/2 , // kn sum
    &AD22100K_wma_buf[0]                    // Xn buffer
};

#else                                          // Non-moving average filter
#endif

#define iDummy_adr      0xffffffff            // Dummy address

const tbl_adc_t tbl_AD22100K =
```

```

{
    iAD22100K          ,
    iAD22100K_pin      ,
    iAD22100K_xoff     ,
    iAD22100K_yoff     ,
    iAD22100K_gain     ,
    iAD22100K_max      ,
    iAD22100K_min      ,
    iAD22100K_ma       ,

    #if iAD22100K_ma == iSMA // Simple moving average filter
        &AD22100K_Phy_SMA ,
        (ema_f32_t*) iDummy_adr ,
        (wma_f32_t*) iDummy_adr
    #elif iAD22100K_ma == iEMA // Exponential moving average filter
        (sma_f32_t*) iDummy_adr ,
        &AD22100K_Phy_EMA ,
        (wma_f32_t*) iDummy_adr
    #elif iAD22100K_ma == iWMA // Weighted moving average filter
        (sma_f32_t*) iDummy_adr ,
        (ema_f32_t*) iDummy_adr ,
        &AD22100K_Phy_WMA
    #else // Non-moving average filter
        (sma_f32_t*) iDummy_adr ,
        (ema_f32_t*) iDummy_adr ,
        (wma_f32_t*) iDummy_adr
    #endif

};

```