

Test Specifications and Results of ADC components

Spec-00000057. pdf

$$v_i = (a_i \times \text{ADC_vdd}) / 2^{\text{ADC_bit}}$$

$$y = (v_i - x_{\text{offset}}) / \text{gain} + y_{\text{offset}} \quad \text{range min to max}$$

$$\text{SMA calculation method} \quad \text{phy} = (y_n + y_{n-1} + y_{n-2}) / n$$

$$\text{EMA calculation method} \quad \text{phy} = (y \times k) + (\text{phy}_{n-1} \times (1 - k))$$

$$\text{WMA calculation method} \quad \text{phy} = ((y_n \times n) + (y_{n-1} \times (n-1)) + \dots + (y_1 \times 1)) / (n + (n-1) + \dots + 1)$$



$$\text{Non-MA calculation method} \quad \text{phy} = y$$

Date	11-Oct-22
Verifier	Red Dragon

Spec-MAX6605MXK. pdf


component data	
x_offset	0.7440 [V]
gain	0.0119 [V/°C]
y_offset	0.0 [°C]
max	125.0 [°C]
min	-55.0 [°C]

Coefficient		
SMA	n	4
EMA	k	0.75
WMA	m	3



Test environment


Board	Mega 2560 Rev3
MPU	ATmega2560
CompilerVer	avr-gcc 7.3.0
IDE	Arduino IDE 1.8.19
Vdd	5.0 [V]
ADC bit	10 [bit]
ADC pin	A0 -
Component	Dummy



Test Method

1. Coupling test with variable resistors

As shown in the figure below, the voltage is varied by a variable resistor to check if the temperature calculation results match the specifications. Non-MA mode:




No.		ADC pin	ai	vi	p	res. phy	res. sts	Judgment
1	Expected	0.000	0	0.000	-62.521	-55.000	4,002	OK
	Measured		0	0.000	-62.521	-55.000	4,002	
	Difference		0	0.000	0.000	0.000	0	
2	Expected	1.500	307	1.499	63.447	63.447	4,000	OK
	Measured		307	1.499	63.447	63.447	4,000	
	Difference		0	0.000	0.000	0.000	0	
3	Expected	2.000	410	2.002	105.710	105.710	4,000	OK
	Measured		411	2.007	106.121	106.121	4,000	
	Difference		-1	-0.005	-0.410	-0.410	0	
4	Expected	5.000	1,024	5.000	357.647	125.000	4,001	OK
	Measured		1,023	4.995	357.237	125.000	4,001	
	Difference		1	0.005	0.410	0.000	0	

res. sts 4,000 Normal
 4,001 Max Limiter NG
 4,002 Min Limiter NG

2. Detail of replacing ADC value test

As shown in the figure below, change the MP layer to the value read from the Dummy table as shown in the test, and perform the following detailed test.



2-1. Max/Min range test

Vary a_i according to Dummy table as shown in the table below, and check Max/Min limiters and diagnostic results. Non-MA mode.

No.		Dummy a_i	v_i	p	res. phy	res. sts	Judgment
1	Expected	20	0.098	-54.315	-54.315	4,000	OK
	Measured	20	0.098	-54.315	-54.315	4,000	
	Difference	0	0.000	0.000	0.000	0	
2	Expected	19	0.093	-54.725	-54.725	4,000	OK
	Measured	19	0.093	-54.725	-54.725	4,000	
	Difference	0	0.000	0.000	0.000	0	
3	Expected	18	0.088	-55.135	-55.000	4,002	OK
	Measured	18	0.088	-55.135	-55.000	4,002	
	Difference	0	0.000	0.000	0.000	0	
4	Expected	19	0.093	-54.725	-54.725	4,000	OK
	Measured	19	0.093	-54.725	-54.725	4,000	
	Difference	0	0.000	0.000	0.000	0	
5	Expected	457	2.231	124.995	124.995	4,000	OK
	Measured	457	2.231	124.995	124.995	4,000	
	Difference	0	0.000	0.000	0.000	0	
6	Expected	458	2.236	125.406	125.000	4,001	OK
	Measured	458	2.236	125.406	125.000	4,001	
	Difference	0	0.000	0.000	0.000	0	
7	Expected	457	2.231	124.995	124.995	4,000	OK
	Measured	457	2.231	124.995	124.995	4,000	
	Difference	0	0.000	0.000	0.000	0	


res. sts 4000 Normal
 4001 Max Limiter NG
 4002 Min Limiter NG

2-2. Moving average test

Check each Filter by changing a_i according to the Dummy table as shown in the table below.


SMA

	No.	Dummy a_i	v_i	p	res. phy	res. sts	Judgment
1	Expected	130	0.635	-9.179	-9.179	4.000	OK
	Measured	130	0.635	-9.179	-9.179	4.000	
	Difference	0	0.000	0.000	0.000	0	
2	Expected	165	0.806	5.182	-5.589	4.000	OK
	Measured	165	0.806	5.182	-5.589	4.000	
	Difference	0	0.000	0.000	0.000	0	
3	Expected	200	0.977	19.543	1.592	4.000	OK
	Measured	200	0.977	19.543	1.592	4.000	
	Difference	0	0.000	0.000	0.000	0	
4	Expected	235	1.147	33.904	12.362	4.000	OK
	Measured	235	1.148	33.904	12.363	4.000	
	Difference	0	0.000	0.000	0.000	0	
5	Expected	270	1.318	48.265	26.724	4.000	OK
	Measured	270	1.318	48.266	26.724	4.000	
	Difference	0	0.000	0.000	0.000	0	
6	Expected	305	1.489	62.627	41.085	4.000	OK
	Measured	305	1.489	62.627	41.085	4.000	
	Difference	0	0.000	0.000	0.000	0	
7	Expected	340	1.660	76.988	55.446	4.000	OK
	Measured	340	1.660	76.988	55.446	4.000	
	Difference	0	0.000	0.000	0.000	0	



EMA

	No.	Dummy ai	vi	p	res. phy	res. sts	Judgment
1	Expected	130	0.635	-9.179	-9.179	4.000	OK
	Measured	130	0.635	-9.179	-9.179	4.000	
	Difference	0	0.000	0.000	0.000	0	
2	Expected	165	0.806	5.182	1.592	4.000	OK
	Measured	165	0.806	5.182	1.592	4.000	
	Difference	0	0.000	0.000	0.000	0	
3	Expected	200	0.977	19.543	15.055	4.000	OK
	Measured	200	0.977	19.543	15.055	4.000	
	Difference	0	0.000	0.000	0.000	0	
4	Expected	235	1.147	33.904	29.192	4.000	OK
	Measured	235	1.148	33.904	29.192	4.000	
	Difference	0	0.000	0.000	0.000	0	
5	Expected	270	1.318	48.265	43.497	4.000	OK
	Measured	270	1.318	48.266	43.497	4.000	
	Difference	0	0.000	0.000	0.000	0	
6	Expected	305	1.489	62.627	57.844	4.000	OK
	Measured	305	1.489	62.627	57.844	4.000	
	Difference	0	0.000	0.000	0.000	0	
7	Expected	340	1.660	76.988	72.202	4.000	OK
	Measured	340	1.660	76.988	72.202	4.000	
	Difference	0	0.000	0.000	0.000	0	



WMA

	No.	Dummy ai	vi	p	res. phy	res. sts	Judgment
1	Expected	130	0.635	-9.179	-9.179	4,000	OK
	Measured	130	0.635	-9.179	-9.179	4,000	
	Difference	0	0.000	0.000	0.000	0	
2	Expected	165	0.806	5.182	-1.999	4,000	OK
	Measured	165	0.806	5.182	-1.999	4,000	
	Difference	0	0.000	0.000	0.000	0	
3	Expected	200	0.977	19.543	9.969	4,000	OK
	Measured	200	0.977	19.543	9.969	4,000	
	Difference	0	0.000	0.000	0.000	0	
4	Expected	235	1.147	33.904	24.330	4,000	OK
	Measured	235	1.148	33.904	24.330	4,000	
	Difference	0	0.000	0.000	0.000	0	
5	Expected	270	1.318	48.265	38.691	4,000	OK
	Measured	270	1.318	48.266	38.691	4,000	
	Difference	0	0.000	0.000	0.000	0	
6	Expected	305	1.489	62.627	53.053	4,000	OK
	Measured	305	1.489	62.627	53.053	4,000	
	Difference	0	0.000	0.000	0.000	0	
7	Expected	340	1.660	76.988	67.414	4,000	OK
	Measured	340	1.660	76.988	67.414	4,000	
	Difference	0	0.000	0.000	0.000	0	

