



Specification document of MPXA4250A

Component manufacturer	NXP Semiconductors		
Model number	MPXA4250A		
Datasheets	https://www.nxp.com/docs/en/data-sheet/MPX4250A.pdf		
Specification Ver	01.00.00	Aug 31,2022	New release
	01.00.01	Sep 10,2022	Corrected license URL
Documentation provided	Rui Long Lab Inc. https://rui-long-lab.com/		

1. Component Software IF specification	2
2. File Structure and Definitions	4

License

Open Source Software for Embedded Components ("OSS-EC") is open source software files and related documentation files for component products used in computer systems and other applications. OSS-EC is provided to those who accept the OSS-EC Terms of Use for the OSS-EC site; see https://oss-ec.com/license_agreement/ for the OSS-EC Terms of Use. By downloading the OSS-EC from the OSS-EC site or obtaining the OSS-EC by any means, you accept the Terms of Use. Please read and accept the Terms of Use before using the OSS-EC. If you do not agree to the Terms of Use, please do not use the OSS-EC. We reserve the right to change these Terms of Use at any time and for any reason. We strongly recommend that you review the Terms of Use periodically.

1. Component Software IF specification

The software interface specifications based on the MPXA4250A component specifications are as follows.

The voltage value-to-physical value conversion equation is a linear conversion equation as shown in the equation below.

ADC value to voltage value conversion formula


$$v_i = (a_i \times i_{ADC_vdd}) / 2^{i_{ADC_bit}} \quad [V]$$

Voltage value to physical value conversion formula

$$y = (v_i - i_{MPXA4250A_xoff}) / i_{MPXA4250A_gain} + i_{MPXA4250A_yoff} \quad [kPa]$$

$$i_{MPXA4250A_min} \leq y \leq i_{MPXA4250A_max}$$

a_i	A/D conversion value	
v_i	Sensor output voltage value [V]	
i_{ADC_vdd}	Sensor supply voltage value [V]	
i_{ADC_bit}	A/D conversion bit length	
y	Pressure value [kPa]	
#define $i_{MPXA4250A_xoff}$	(<u>-0.04F</u> * i_{ADC_vdd})	// X offset [V]
#define $i_{MPXA4250A_yoff}$	<u>0.0F</u>	// Y offset [kPa]
#define $i_{MPXA4250A_gain}$	(<u>0.004F</u> * i_{ADC_vdd})	// Gain [V/kPa]
#define $i_{MPXA4250A_max}$	<u>250.0F</u>	// Pressure Max [kPa]
#define $i_{MPXA4250A_min}$	<u>20.0F</u>	// Pressure Min [kPa]



2. File Structure and Definitions

MPXA4250A.h

```
#include "user_define.h"

// Components number
#define IMPXA4250A          100U          // NXP MPXA4250A

// MPXA4250A System Parts definitions
#define IMPXA4250A_xoff      ( -0.04F*iADC_vdd )    // X offset [V]
#define IMPXA4250A_yoff      0.0F                  // Y offset [kPa]
#define IMPXA4250A_gain      ( 0.004F*iADC_vdd )    // Gain [V/kPa]
#define IMPXA4250A_max        250.0F                // Pressure Max [kPa]
#define IMPXA4250A_min        20.0F                 // Pressure Min [kPa]

extern const tbl_adc_t tbl_MPX4250A;
```

MPXA4250A.cpp

```
#include      "MPXA4250A.h"

#if      iMPXA4250A_ma == iSMA                                // Simple moving average filter
static float32 MPXA4250A_sma_buf[iMPXA4250A_SMA_num];
static const sma_f32_t MPXA4250A_Phy_SMA =
{
    iInitial ,                                                // Initial state
    iMPXA4250A_SMA_num ,                                       // Simple moving average number & buf
size
    0U ,                                                        // buffer position
    0.0F ,                                                      // sum
    &MPXA4250A_sma_buf[0]                                       // buffer
};

#elif      iMPXA4250A_ma == iEMA                                // Exponential moving average filter
static const ema_f32_t MPXA4250A_Phy_EMA =
{
    iInitial ,                                                // Initial state
    0.0F ,                                                      // Xn-1
    iMPXA4250A_EMA_K                                           // Exponential smoothing factor
};

#elif      iMPXA4250A_ma == iWMA                                // Weighted moving average filter
static float32 MPXA4250A_wma_buf[iMPXA4250A_WMA_num];
static const wma_f32_t MPXA4250A_Phy_WMA =
{
    iInitial ,                                                // Initial state
    iMPXA4250A_WMA_num ,                                       // Weighted moving average number & buf
size
    0U ,                                                        // buffer position
    iMPXA4250A_WMA_num * (iMPXA4250A_WMA_num + 1)/2 , // kn sum
    &MPXA4250A_wma_buf[0]                                       // Xn buffer
};

#else                                                        // Non-moving average filter
#endif

#define iDummy_adr      0xffffffff                          // Dummy address
```

```
const tbl_adc_t tbl_MPX4250A =
{
    iMPXA4250A          ,
    iMPXA4250A_pin      ,
    iMPXA4250A_xoff     ,
    iMPXA4250A_yoff     ,
    iMPXA4250A_gain     ,
    iMPXA4250A_max      ,
    iMPXA4250A_min      ,
    iMPXA4250A_ma       ,

    #if iMPXA4250A_ma == iSMA // Simple moving average filter
        &MPXA4250A_Phy_SMA ,
        (ema_f32_t*) iDummy_adr ,
        (wma_f32_t*) iDummy_adr
    #elif iMPXA4250A_ma == iEMA // Exponential moving average filter
        (sma_f32_t*) iDummy_adr ,
        &MPXA4250A_Phy_EMA ,
        (wma_f32_t*) iDummy_adr
    #elif iMPXA4250A_ma == iWMA // Weighted moving average filter
        (sma_f32_t*) iDummy_adr ,
        (ema_f32_t*) iDummy_adr ,
        &MPXA4250A_Phy_WMA
    #else // Non-moving average filter
        (sma_f32_t*) iDummy_adr ,
        (ema_f32_t*) iDummy_adr ,
        (wma_f32_t*) iDummy_adr
    #endif
};
```