

PN512 NFC Reader based on Arduino v1.2

Table of contents

About	3
Library	4
Modifying the library	4
Hardware	9
Pinout	9
Revision history	11

About

With the assistance of the PN512 chip, the PN512 NFC Reader can read cards and tags in addition to sharing pinouts and other features with the Arduino Nano. Since it is intended to replace the RFID-RC522 module, the RFID-MFRC522 and PN512 share the same functionality.

Library

To use the device you will need a RFID library. We have modified an, already known, library for the MFRC-522 RFID Reader to work with the PN512 chip. The library that was used was miguelbalboa's rfid library, <https://github.com/miguelbalboa/rfid>.

You will find the PN512 library in the official Arduino Library Manager in the Arduino IDE application, or you can find it on our github,

https://github.com/nfc-rfid-reader-sdk/MFRC522_PN512/.

If you want to make your own changes to the library, the necessary steps required to initialize the PN512's registers to work with the MFRC522 library are explained in this document.

Modifying the library

First, in the "*mfrc522.h*" file, add the PN512 self-test firmware reference:

```
//PN512 (0x82)
const byte PN512_firmware_reference[] PROGMEM = {
    0x00, 0xEB, 0x66, 0xBA, 0x57, 0xBF, 0x23, 0x95,
    0xD0, 0xE3, 0x0D, 0x3D, 0x27, 0x89, 0x5C, 0xDE,
    0x9D, 0x3B, 0xA7, 0x00, 0x21, 0x5B, 0x89, 0x82,
    0x51, 0x3A, 0xEB, 0x02, 0x0C, 0xA5, 0x00, 0x49,
    0x7C, 0x84, 0x4D, 0xB3, 0xCC, 0xD2, 0x1B, 0x81,
    0x5D, 0x48, 0x76, 0xD5, 0x71, 0x61, 0x21, 0xA9,
    0x86, 0x96, 0x83, 0x38, 0xCF, 0x9D, 0x5B, 0x6D,
    0xDC, 0x15, 0xBA, 0x3E, 0x7D, 0x95, 0x3B, 0x2F
};
```

1. Self-test firmware reference that will be added

In the "mfr522.cpp" file on line 326 (at the end of the *switch-case* function) , expand the function "PCD_PerformSelfTest()" with the following case:

```
case 0x82: // PN512
reference = PN512_firmware_reference;
break;
```

2. Addition of a case statement for the "PCD_PerformSelfTest()"

These code changes should resemble the following:

```
64 };
65 // Clone
66 // Fudan Semiconductor FM17522 (0x88)
67 const byte FM17522_firmware_reference[] PROGMEM = {
68     0x00, 0xD6, 0x78, 0x8C, 0xE2, 0xAA, 0x0C, 0x18,
69     0x2A, 0xB8, 0x7A, 0x7F, 0xD3, 0x6A, 0xCF, 0x0B,
70     0xB1, 0x37, 0x63, 0x4B, 0x69, 0xAE, 0x91, 0xC7,
71     0xC3, 0x97, 0xAE, 0x77, 0xF4, 0x37, 0xD7, 0x9B,
72     0x7C, 0xF5, 0x3C, 0x11, 0x8F, 0x15, 0xC3, 0xD7,
73     0xC1, 0x5B, 0x00, 0x2A, 0xD0, 0x75, 0xDE, 0x9E,
74     0x51, 0x64, 0xAB, 0x3E, 0xE9, 0x15, 0xB5, 0xAB,
75     0x56, 0x9A, 0x98, 0x82, 0x26, 0xEA, 0x2A, 0x62
76 };
77
78
79 //PN512 (0x82)
80 const byte PN512_firmware_reference[] PROGMEM = {
81     0x00, 0xEB, 0x66, 0xBA, 0x57, 0xBF, 0x23, 0x95,
82     0xD0, 0xE3, 0x0D, 0x3D, 0x27, 0x89, 0x5C, 0xDE,
83     0x9D, 0x3B, 0xA7, 0x00, 0x21, 0x5B, 0x89, 0x82,
84     0x51, 0x3A, 0xEB, 0x02, 0x0C, 0xA5, 0x00, 0x49,
85     0x7C, 0x84, 0x4D, 0xB3, 0xCC, 0xD2, 0x1B, 0x81,
86     0x5D, 0x48, 0x76, 0xD5, 0x71, 0x61, 0x21, 0xA9,
87     0x86, 0x96, 0x83, 0x38, 0xCF, 0x9D, 0x5B, 0x6D,
88     0xDC, 0x15, 0xBA, 0x3E, 0x7D, 0x95, 0x3B, 0x2F
89 };
90
91 class MFRC522 {
92 public:
93     // Size of the MFRC522 FIFO
94     static constexpr byte FIFO_SIZE = 64; // The FIFO is 64 bytes.
95     // Default value for unused pin
96     static constexpr uint8_t UNUSED_PIN = UINT8_MAX;
```

3. added the self-test reference, preview

```

373
374 // Pick the appropriate reference values
375 const byte *reference;
376 switch (version) {
377     case 0x88: // Fudan Semiconductor FM17522 clone
378         reference = FM17522_firmware_reference;
379         break;
380     case 0x90: // Version 0.0
381         reference = MFRC522_firmware_referenceV0_0;
382         break;
383     case 0x91: // Version 1.0
384         reference = MFRC522_firmware_referenceV1_0;
385         break;
386     case 0x92: // Version 2.0
387         reference = MFRC522_firmware_referenceV2_0;
388         break;
389     case 0x82: // PN512
390         reference = PN512_firmware_reference;
391         break;
392     default: // Unknown version
393         return false; // abort test
394 }
395

```

4. added case at the end of the *switch-case*

And in the *PCD_DumpVersionToSerial()* in the "mfrc522.h" file, add the following *switch-case* line.

```
case 0x82: Serial.println(F(" = PN512")); break;
```

```

1391
1392 void MFRC522::PCD_DumpVersionToSerial() {
1393     // Get the MFRC522 firmware version
1394     byte v = PCD_ReadRegister(VersionReg);
1395     Serial.print(F("Firmware Version: 0x"));
1396     Serial.print(v, HEX);
1397     // Lookup which version
1398     switch(v) {
1399         case 0x88: Serial.println(F(" = (clone)")); break;
1400         case 0x90: Serial.println(F(" = v0.0")); break;
1401         case 0x91: Serial.println(F(" = v1.0")); break;
1402         case 0x92: Serial.println(F(" = v2.0")); break;
1403         case 0x12: Serial.println(F(" = counterfeit chip")); break;
1404         case 0x82: Serial.println(F(" = PN512")); break;
1405         default: Serial.println(F(" = (unknown)"));
1406     }
1407     // When 0x00 or 0xFF is returned, communication probably failed
1408     if ((v == 0x00) || (v == 0xFF))

```

5. added version in the *switch-case* function



Next, it would be necessary to add the following 3 registers in the *PCD_Register* list:

```
TypeBReg      = 0x1E << 1,    // Configure the ISO/IEC 14443 type B

GsNOffReg      = 0x23 << 1,    // Selects the conductance of the antenna
driver pin TX1 and TX2 for modulation, when the driver is switched off

TxBitPhaseReg  = 0x25 << 1,    // Adjust the TX bit phase at 106 kbit
```

6. Registers for *PCD_Register* list

These registers are “Reserved for future use” in the MFRC522 chip, but are used in PN512 chips.

The final step is to initialize the new registers and more in the “*PCD_Init()*” function in the “*MFRC522.cpp*” file. Initializing these registers enables the chip to work properly.

```
{  
    PCD_WriteRegister(TxModeReg, 0x00);  
    PCD_WriteRegister(RxModeReg, 0x00);  
    PCD_WriteRegister(ModWidthReg, 0x26);  
  
    PCD_WriteRegister(TxASKReg, 0x40);  
    PCD_WriteRegister(RxThresholdReg, 0xFF);  
    PCD_WriteRegister(ControlReg, 0x10);  
    PCD_WriteRegister(DemodReg, 0x4D);  
    PCD_WriteRegister(MfTxReg, 0x62);  
    PCD_WriteRegister(TxBitPhaseReg, 0x87);  
    PCD_WriteRegister(RxSelReg, 0x84);  
    PCD_WriteRegister(RFCfgReg, 0x48);  
    PCD_WriteRegister(GsNReg, 0x88);  
    PCD_WriteRegister(CWGsPReg, 0x20);  
    PCD_WriteRegister(GsNOffReg, 0x88);  
    PCD_WriteRegister(ModGsPReg, 0x20);  
  
    PCD_WriteRegister(ModeReg, 0x3D);  
    PCD_WriteRegister(BitFramingReg, 0x00);  
    PCD_WriteRegister(WaterLevelReg, 64);  
    PCD_WriteRegister(TypeBReg, 0);  
    PCD_WriteRegister(MfTxReg, 0x8A);  
    PCD_AntennaOn();  
} // End PCD_Init()
```

7. Initialization of the registers

After all of these modifications, the device will work properly.

For further assistance, we made some examples for how you would use the device on our github:



https://github.com/nfc-rfid-reader-sdk/MFRC522_PN512/tree/master/examples/PN512

In addition to these PN512 examples, the original examples for the MFRC522 can be found in the *"/examples/MFRC522"* directory.

Hardware

Pinout

Pin Number	Pin Name	Mapped Pin Name	Pin Number	Pin Name	Mapped Pin Name
1	PC7	Digital pin 13	16	PD6	Digital pin 12
2	3.3V	3.3V	17	PB7	Digital pin 11
3	AREF	REF	18	PB6	Digital pin 10
4	PF0	Analog pin 0	19	PB5	Digital pin 9
5	PF1	Analog pin 1	20	PB4	Digital pin 8
6	PE6	Analog pin 2	21	PE6	Digital pin 7
7	PD7	Analog pin 3	22	PD7	Digital pin 6
8	PF4	Analog pin 4	23	PC6	Digital pin 5
9	PF5	Analog pin 5	24	PD4	Digital pin 4
10	PF6	Analog pin 6	25	PD0	Digital pin 3
11	PF7	Analog pin 7	26	PD1	Digital pin 2
12	VCC	5V	27	GND	GND
13	Reset	RST	28	Reset	RST
14	GND	GND	29	PD3	RX
15	VCC	5V	30	PD2	TX



8. Pinout and proportions of the PN512 NFC reader

Revision history

Date	Version	Comment
2023-08-03	1.2	URL references updated; About section updated; Modifying the library section was added
2023-08-03	1.1	Document format updated
2023-08-01	1.0	Base document