


Arduino/ESP 32 Microcontrollers

ez_switch_lib - Switch Library User Guide

A Library Supporting the Reading of Multiple
Mixed-type Simple Switches & Circuits
with Arduino & ESP 32 Microcontrollers



Warranties & Exceptions

This document and its content are in the public domain and may be used without restriction and without warranty.

Change Record

Doc Ref / Version	Date	Change
1.02	March 2021	Initial version published
1.03	March 2021	Addition of new library variable (<code>last_switched_id</code>), plus example of its use in sketch with multiple buttons all linked to a single interrupt handler.
1.04	July 2021	Correction to Corollary ISR example.
3.00	Sept 2022	Addition of new library functions – <code>reset_switch</code> , <code>reset_switches</code> , <code>button_is_pressed</code> (overloaded function).
3.01	Sept 2022	Change of library variables to unsigned declarations, generally, eg <code>byte</code> to <code>uint8_t</code> , <code>long unsigned int</code> to <code>uint32_t</code> , etc

Contents

Warranties & Exceptions	2
Change Record	2
Introduction.....	4
Overview	4
Design Objectives	5
Constraints & Limitations	5
Switch Types Supported	6
Common Switch Wiring Schemes.....	7
Using the <ez_switch_lib> Library	8
To Know... ..	8
Accessing the <ez_switch_lib> Library	10
Steps to Successful Use	10
Specifications	14
Specifications – Switch Control Structure (SCS)	14
Specifications - Reserved Macro Definitions and Other Declarations	14
Other Declarations	15
Specifications - Switch Control Functions.....	16
add_switch	16
link_switch_to_output	17
num_free_switch_slots	18
read_switch	18
read_button_switch	19
read_toggle_switch	19
reset_switch	20
reset_switches	20
button_is_pressed	21
button_is_pressed	22
print_switch	23
print_switches	24
set_debounce	24
Example Sketches	25
Example 1.1 - Turning LED On/Off With a Button Switch, Directly Coded	26
Example 1.2 - Turning LED On/Off With a Button Switch, Indirectly Coded	28
Example 2.1 - Turning LED On/Off With a Toggle Switch, Directly Coded	30
Example 2.2 - Turning LED On/Off With a Toggle Switch, Indirectly Coded	32
Example 3.1 - Turning Multiple LEDs On/Off With Multiple Button & Toggle Switches, Directly Coded.....	34
Example 3.2 - Turning Multiple LEDs On/Off With Multiple Button & Toggle Switches, Indirectly Coded.....	37
Example 4 – Processing More Button & Toggle Switches.....	40
Example 5 – Using the Libraries Switch Structure Variables.....	46
Corollary	49
Switch Mismatching	49
Buttons as a Toggles	49
Many Switches, One Interrupt Service Routine (ISR).....	51

Introduction

Implementing switches, of any type, can be troublesome as not all switches are equal! Some are 'fleeting' or momentary, like button switches, and some are simply either on or off until they are 'flipped' at their next actuation. Button switches are fairly standard in their design, but toggle type switches are many varied – simple toggle, slide, tilt, rotary, etc. If you are incorporating switches into your projects then issues such as switch design, transition 'noise' and wiring schemes will all come into play at some point in a project's design.

The good news is that both types of switch can be brought to heel by the `<ez_switch_lib>` library which provides a simple to use, no frills, software solution for connecting a mix of switch types wired in a variety of circuit schemes. The end result is that, by using the `<ez_switch_lib>`, the only components required are switches, connecting wires and, *if wished*, 10k ohm pull down resistors. However, even the 10k ohm resistors can be left out by choice of the right circuit (see below, Common Switch Wiring Schemes).

This User Guide (UG) describes the `<ez_switch_lib>` library for Arduino and ESP 32 microcontrollers, detailing the functions and definitions available to the end user for implementing switches of either style and in a choice of wiring schemes - any number of switches of any style and of varying common wiring designs may be configured, the only limitation being the number of digital pins available.

However, before continuing, if you would like to understand a little about the issues associated with switches have a look at the tutorial [Understanding & Using Button Switches](#). Although it is centred on the simple button switch, the basics are also common to toggle switches. A supplementary document is also available to accompany this User Guide designed to offer a 'quick start' to understanding how to use the library – see [Quick Start Guide](#).

Overview

This UG provides information and guidance that will prove helpful in understanding the capabilities of the switch library, `<ez_switch_lib>`, in designing and implementing projects using switches, single or multiple of varying types.

The UG gives information and explanations of:

- Design objectives what was sought.
- Constraints & limitations it is vitally important to understand any constraints and limitations that the library imposes/suffers, as these may play a part in the way in which you utilise the library.
- Types of switch supported there are many types of switch available. Those suitable for use with the library are highlighted.
- Common wiring schemes again there are many ways in which a switch may be wired. The library has been designed to support the two of the most common wiring schemes to be used for any switch type. The approach is to minimise any additional hardware components used.
- Using the library describes how the library should be (can be) incorporated into your

projects.

- **Declarations & definitions** provides a list of all of the library's switch macro definitions and control struct(ure) available to the end user to incorporate into their sketches.
- **Function specifications** each of the library's functions is detailed with an example in its use. Any specific points of note are also provided.
- **Example sketches** example sketches are provided, building from single button and toggle switches to multiple switch types using both circuit schemes and using different programming techniques to declare and use switch data.

An accompanying Crib Sheet is also available and, hopefully, it and this UG will become a 'one-stop-shop' to help the end user supplement understanding in the application of switches and the library's capabilities.

Design Objectives

At the outset a number of key objectives were established for the design of the switch library, these being a library that provided/supported:

- a simple, logical and straight forward design
- ease of end user project switch configuration, irrespective of type and number of switches or how connected (wired)
- different switch types - the ubiquitous button switch and a variety of different types of toggle switch
- support for common wiring schemes – simply connected with or without a 10k ohm pull down resistor
- mixed switch/circuit implementations – support for a mix of switch types and wiring schemes
- software auto-debounce of noisy switch transitions – removing from end user design consideration issues relating to noisy switch transition by incorporating transparent debounce features
- one switch read function irrespective of switch type or wiring scheme – providing a simple to use function to read any and all switches
- allowing the optional linking of switches to a digital output such that auto-switching of the output can occur without end user programmatic coding
- developing a user guide that is informative and such that it is easy to 'dip' into.

Constraints & Limitations

Nothing in this world is perfect and `<ez_switch_lib>` is far from that. Whilst it does provide a set of useful capabilities to aid and assist Arduino project developers involving switches, there are several constraints and limitations in its design and use to be aware of:

1. Every switch to be configured requires its own digital pin. Whilst this is not an issue for say, a mega 2560 microcontroller, lesser boards are more constraining in the number of

digital pins they support. Certainly for UNO microcontrollers and better, there should not be a practical issue in mapping switches to digital pins for most switch hungry projects.

2. Development of the library was limited to six switches (see `ez_switch_lib` Example 4)
 - two x button switches wired with a 10k ohm pull down resistor
 - one x button switches wired without a 10k ohm pull down resistor
 - two x toggle switches wired without a 10k ohm pull down resistor
 - one x toggle switches wired with a 10k ohm pull down resistor

but, there is no reason to believe that more could not be configured within the limits of the chosen microcontroller.

3. For every switch configured, 12 uint8_ts of free memory will be allocated at run time when the `<ez_switch_lib>` class is initiated. This memory requirement is in addition to the size of the compiled sketch.
4. The period of time defined for switch noise debounce is global and applicable to all switches, irrespective of type. It is preset 'out of the box' (OOTB) to 10 milliseconds but it may be programmatically adjusted by the end user code, as required (see function `set_debounce`, below).
5. The library supports two simple and commonly seen switch wiring schemes (see Common Switch Wiring Schemes), these being without the use of any hardware components other than, optionally, 10k ohm resistors. Even these can be dispensed with! Having said that, the library should also support (but not tested) switches connected with hardware debounce circuits. If this is the case then set the software debounce period to 0 milliseconds (see function `set_debounce`, below).
6. For switches to be responsive in something like real-time, they need to be tested frequently and, for button switches particularly, processed when a switch cycle is detected. However, toggle switches may have their current status examined at any point and any time. A software design based on a switch polling loop should be an ideal harness to ensure continuous switch testing and processing.

Switch Types Supported

There are so, so many switches available, many for specific purposes but most of a general nature and suitable for the majority of needs.

The switch library was developed to support two types of common and general use switches – button, or momentary switches, and toggle switches. Of course this latter type of switch, toggle, itself comes in all kinds of designs, for example, simple single lever, pop-on pop-off, rotary, slide, tilt, etc.




Examples of common types of switch

The principal distinction between button (momentary) and toggle type switches is that button switches have a switch cycle of OFF-ON-OFF which signifies switch activation, whereas toggle switches go through either OFF-ON or ON-OFF representing two distinct and separate switch transitions. The status of toggle switches therefore persists after being physically switched – they stay ON or OFF. <ez_switch_lib> automatically handles these physical characteristics.

Common Switch Wiring Schemes


If you now appreciate the differences between switch types, it is necessary to understand how they should be connected to the microcontroller and the differences between commonly seen switch wiring schemes without hardware debounce.

For Arduino AND ESP 32 microcontrollers:



Arduino Microcontroller


Figure 1 – Circuit C1



Arduino Microcontroller

Figure 2 – Circuit C2

And for ESP2 microcontrollers only:



ESP 32 Microcontroller

Figure 3 – circuit_C3,
(INPUT_PULLDOWN)

Note:
ESP32 operates at 3.3v

All circuit styles can be used for either type of switch, but the key to configuring correctly lies in the way they are software configured via the `pinMode` function, as follows.

- **circuit_C1** (Arduino AND ESP 32) - the `pinMode` setting for initialising **circuit_C1** is `pinMode(<pin>, INPUT)`. This has the effect of setting the digital pin <pin> to 0v, representing 'off'. The 10k ohm pull down resistor is essential and ensures that the pin stays at 0v until switched, otherwise the input pin will be susceptible to spurious firing from extraneous fields. When the switch is actuated the input rises to +5v which will be detected as the switch transitioning to 'on'.
- **circuit_C2** (Arduino AND ESP 32) - the `pinMode` setting is `pinMode(<pin>, INPUT_PULLUP)`. This brings into play an internal microcontroller pull up resistor resulting in the digital pin floating at 5v, representing 'off'. No external resistor is required and when the switch is actuated the pin will be brought to 0v which will be detected as the switch transitioning to 'on'.
- **circuit_C3** (ESP 32 only)- the `pinMode` setting is `pinMode(<pin>, INPUT_PULLDOWN)`. This brings into play an internal microcontroller pull down resistor resulting in the digital pin being at 0v, representing 'off'. Like **circuit_C1**, when the switch is actuated the input rises to +5v which will be detected as the switch transitioning to 'on'. Note that if **circuit_C3** is referenced in a sketch and compiled for an Arduino microcontroller then this will be converted to **circuit_C1** (i.e. `INPUT`).

Using the `<ez_switch_lib>` Library

To Know...

The switch reading functions of the library `<ez_switch_lib>` are functions that read the microcontroller's digital pins as inputs. At the heart of these functions lies the use of the general `digitalRead` function. So, if that is the case, why do we need other functions to read digital pins?

Well, there are several reasons:

- not all switches are the same, there is a difference between how button and toggle switches behave
- when switches transition to on/off, off/on (toggle switches) or off/on/off (button switches) they do so in a small finite time during which they will often generate 'noise' which can be read as a spurious signal and confuse the calling code logic
- switches may be wired in different ways which can reverse the logical understanding what the meaning of 'on' and 'off' - depending on the wiring scheme, a `LOW` signal can mean 'on' and a `HIGH` signal 'off' and vice versa.

In short, and as previously stated, switches can be troublesome for the uninitiated! The `<ez_switch_lib>` library switch read functions deal with all of the above issues, so we can concentrate purely on what we want switches to do for us.

Both the `digitalRead` and the `<ez_switch_lib>` library switch read functions test a digital pin at a point in time and in a non-blocking way (they have a 'quick look' and immediately move on – returning back to the calling code). The downside of non-blocking functionality means that digital pins with switches connected must be regularly tested if switch actuations are not to be missed. In fact, they should all be tested at every

opportunity. If you look at the Example Sketches 1.1 – 4, they are all designed to constantly poll every switch at every main loop cycle. It is in this way that we are able to ensure the code can keep up with what is happening the real world, without missing a switch actuation.

There are three `<ez_switch_lib>` library functions we can use to read a switch, once it is declared to the library class. These are:

- `read_button_switch`
- `read_toggle_switch`
- `read_switch`

All have the same single parameter (switch id) and return values (see Specifications - Switch Control Functions) but behave in different ways.

The first two functions are obvious in their purpose – they allow us to read (test) a button switch and toggle switch respectively. However, the third function, `read_switch`, is ‘agnostic’ and may be used without regard to what type of switch is connected. It should be the principal read function in use in your sketch as it will manage switch type itself. This function also has other capabilities involving linked outputs (see later).

All of these functions return a value of `switched` or `!switched` (not switched), a little like the `digitalRead` return values of `HIGH` and `LOW`.

However, the `<ez_switch_lib>` library functions provide additional information that is useful to the programmer:

- For button switches, the programmer can access a library variable that will indicate if a button switch is in transition (off-on-off cycle active and pending completion). The library variable is `<class name>.switches[switch_id].switch_pending`, where `<class name>` is the name you have given to the library’s **Switches** class when you declared/initiated it. The permissible values of this variable are either `true` or `false`. For example:

```
my_switches.read_switch(button_id); // test switch
if (my_switches.switches[button_id].switch_pending == true) {
    // switch is in transition, so take it as on until not pending...
}
```

Alternatively, with version 3.00, we also have a supplemental and specific function for testing switch transition (button switches ONLY) – `button_is_pressed`. See the description of this function below and how it may be used.

- For toggle switches, we also have access to the same switch pending, switch in transition, variable as above, but also an additional one. Recall that toggle switches are either one state (on/off) or the other until they are actuated (flipped). We therefore need to be able to test what the current/now setting of a toggle switch may be, that is, its current status. We may similarly do this as follows:

```
my_switches.read_switch(toggle_id); // test switch
if(my_switches.switches[toggle_id].switch_status == on){
    // switch is currently on...
}
```

The permissible values of this variable are `on` or `!on` (off).

See Example 5 which shows a sketch employing the above to implement a routine to increment hours and minutes of an external clock/timer, working both in single-shot and continuous advance modes.

Finally, the two `<ez_switch_lib>` library functions - `read_button_switch` and `read_toggle_switch`, will operate in the same way as `read_switch` but specifically for each type of switch only. In addition, if you use these two read functions and your switches have linked outputs then these outputs will not be processed. Only the `read_switch` function will process any linked switch output (see Specifications - Switch Control Functions).

Hopefully, you are now better informed to make good use of the `<ez_switch_lib>` library and its data structures and functions, all of which are documented below – see Specifications and Example Sketches.

Accessing the `<ez_switch_lib>` Library

The `ez_switch_lib` library (plus all of its documentation) is available as a download via the Arduino IDE Library Manager. Select Tools/Manage Libraries and the specify “`ez_switch_lib`” in the dialogue box to download the latest version.

Steps to Successful Use

Before ‘fighting to task’, it is recommended to think carefully about what it is you wish to achieve, how switches are incorporated into your project and how `<ez_switch_lib>` can be utilised.

The principal considerations are:

1. Which microcontroller will be used?
2. Decide how many switches and of what type these will be.
3. For each switch decide –
 - a. which digital pin will be used?
 - b. how will the switch be wired, `circuit_C1`, `circuit_C2` or `circuit_C3`
 - c. do we wish to create a link from the switch to a digital output pin and, if so, what state should the output pin be initialised to at creation time?
4. What will happen when each switch is activated? This step is beyond this UG and is the purpose of your project.

If you are implementing many switches then it may be helpful to make a note of their configurations as once you start wiring and coding things can get a bit muddled up! The following template may be helpful to fill out at the start of your planning and for you to refer to into the development stage (it is also a useful documentation aid post implementation):

Project Name:						MCU:				Date:			
Switch Configs					Linked Outputs				Notes				
Pin	Switch Type		Circuit Type		Pin	Initial Value							
	Button	Toggle	C1	C2		LOW	HIGH						

(add more rows as needed)

For example, Example 4, below, configures the following switches, pins, circuits and links:

Project Name:		LEDs & Relays				MCU:		Arduino UNO		Date:		4 March 2021	
Switch Configs					Linked Outputs			Notes					
Pin	Switch Type		Circuit Type		Pin	Initial Value							
	Button	Toggle	C1	C2		LOW	HIGH						
2		X	X		8		X	Relay 1 - no switching coding					
3		X		X	9	X		Led 1 - no switching coding					
4		X	X					Led 3 - needs switching coding					
5	X			X				Produces switch status report to serial monitor					
6	X		X		10		X	Relay 2 - no switching coding					
7	X			X	11	X		Led 2 - no switching coding					

Having got to grips with what switches, pins and circuit schemes your project will be designed around it is necessary to understand how `<ez_switch_lib>` can be used. As with all libraries there are a number of points to consider:

1. We need to ensure our sketch references the library
2. We need to create an instance of the library class, and
3. We need to understand how to correctly use the library's capabilities (e.g. functions and data).

There are a number of steps to be followed –

Step 1

To start, we need to declare the `<ez_switch_lib>` library. At the top level of your sketch include the following statements:

```
#include <Arduino.h>
#include <ez_switch_lib.h>
```

Step 2

Then, prior to `setup()`, declare how many switches your sketch will be configured for (e.g. `#define num_switches 6`, or `uint8_t num_switches = 6`; etc) together with your switch configuration data (as per the above template?). How you wish to declare this data is very much up to your personal preference. The example sketches, below, show several approaches that you may find instructive.

Step 3

Again, prior to your sketch `setup()` function and after your switch data declarations, add the following class instantiation statement:

```
Switches my_switches(num_switches);
```

Where 'my_switches' is the name you wish to use for the class you have initiated – this can be anything, but 'my_switches' is a pretty good name.

Step 4

Okay, we're off and running? Not quite, before we can plough on and start reading switches we need to declare them to the library along with their attributes. We do this by using the function `add.switch`. This function will add a specified switch to the library's table of active switches such that when it is read (tested) by the read function(s) it will know how it is to be handled. Therefore for each switch you wish to configure you will need to add it to the library's active switch table; for this we use the `add.switch` function:

```
uint8_t switch_id;  
switch_id = my_switches.add.switch(button_switch, 4, circuit_C2);
```

Things to notice:

- the `add.switch` function call is preceded with the name we have given to the **Switches** class, in this example 'my_switches'. This is required to access any resource within the class
- 'button_switch' and 'circuit_C2' are reserved keywords and are highlighted in blue. They each define the switch and circuit type, respectively. There are a number of reserved words you may use throughout your sketch, see Specifications - Reserved Macro Definitions and Switch Control Functions `add.switch` to understand the possible parameters and return values/conditions
- the function provides a return value. If the addition is successful, this value is the reference you should use whenever you use any of the library resources where switch reference is a required parameter. How you retain this is very much up to your design, but see the example sketches below which should prove helpful. See Specifications - Switch Control Functions `add.switch` to understand the possible return values/conditions.

The best place to add/create your switches is in the `setup()` function, but it can be done anywhere so long as it is only done once and is in scope of the library class statement.

Step 5

Now that is done we can start to read the switches.

The simplest way to read a switch is to use the function `read_switch`. This function is agnostic to switch type and has a single parameter - the id of the switch we wish to read. It will return either 'switched' or '!switched' (again reserved library macros), the meaning being obvious. For example:

```
if(my_switches.read_switch(switch_id) == switched)
{
    ...do something;
}
```

There are other resources available from the library and these are described below.

Example - to recap the steps (five) in order of application/use are:

Step	Example
1	<pre>#include <Arduino.h> #include <ez_switch_lib.h> // plus any other libraries</pre>
2	<pre>#define num_switches 1 // number of switches to be added, 1 in this example // define your switch data uint8_t switch_id; uint8_t button_pin = 4; ...</pre>
3	<pre>// create switch class instance Switches my_switches(num_switches); ...</pre>
4	<pre>void setup(){ ... // declare your switches to the library, for example: switch_id = my_switches.add_switch(button_switch, button_pin, circuit_C2); // validate return value... }</pre>
5	<pre>void loop(){ do{ if(my_switches.read_switch(switch_id) == switched) {...do something; } while (true); }</pre>

Additionally to note:

If you need to reference any of the library's class resources (except macros definitions) then you must prefix them with the name you have given to the class when you created/initiated it. For example, if we initiated the class with the name 'my_switches' then:

```
my_switches.switches[switch_id].switch_type
my_switches.switches[2].switch_status
my_switches.switches[toggle_id3].switch_pending
my_switches.add_switch(button_switch, 12, circuit_C2)
my_switches.num_free_switch_slots()
my_switches.set_debounce(25)
my_switches.read_switch(my_switch_data[sw])
switch_id = my_switches.last_switched_id
etc.
```

Specifications

Specifications – Switch Control Structure (SCS)

At the heart of the <ez_switch_lib> library lies a struct(ure) 'table' - the switch control structure (SCS), that is used to hold the data attributes for all declared/defined switches.

At initiation of the class, the SCS is created from free memory using a malloc call of sufficient size to match the number of switches the class is being defined for. Thereafter, it may be populated with switches by use of the `add_switch` function (see below) up to the maximum number of switches declared for the class.

The SCS has the following construction and layout:

```
struct switch_control {  
  
    uint8_t    switch_type;           // type of switch connected  
    uint8_t    switch_pin;           // digital input pin assigned to the switch  
    uint8_t    switch_circuit_type;  // the type of circuit wired to the switch  
    bool       switch_on_value;      // used for BUTTON SWITCHES only -  
                                     // defines what 'on' means  
    bool       switch_pending;       // records if switch in transition or not  
    uint32_t   switch_db_start;      // records debounce start time  
                                     // when associated switch starts transition  
    bool       switch_status;        // used for TOGGLE SWITCHES only - current  
                                     // state of toggle switch.  
    uint8_t    switch_out_pin;       // the digital pin mapped to this switch,  
                                     // if any  
    bool       switch_out_pin_status; // the status of the mapped pin  
}
```

Members of the SCS may be directly accessed from the end user sketch, as required, see above. Of particular interest will be:

For button and toggle switches -

```
my_switches.switches[switch_id].switch_pending
```

and for toggle switches only –

```
my_switches.switches[2].switch_status
```

Specifications - Reserved Macro Definitions and Other Declarations

The table below documents the library's reserved macro definitions. These are available for use by a sketch simply by referencing their name (column 1 and no prefix required), see example sketches. When used they will be coloured in red to show that they are reserved words.

Macro Definitions #define	Values	Significance / Comments
<code>button_switch</code>	1	differentiates switch type, this being of type 'button'
<code>toggle_switch</code>	2	differentiates switch type, this being of type 'toggle'
<code>circuit_C1'</code>	<code>INPUT</code>	switch circuit should be configured <u>with</u> an external pull down 10k ohm resistor
<code>circuit_C2</code>	<code>INPUT_PULLUP</code>	switch circuit should be configured <u>without</u> an

Macro Definitions #define	Values	Significance / Comments
		external pull down resistor. Instead the MCU internal pull-up resistor enabled
<code>circuit_C3</code>	<code>INPUT_PULLDOWN</code>	switch circuit should be configured with internal MCU pull down resistor enabled. NOTE: not applicable for Arduino MCUs, but ESP 32 MCUs. If selected with an Arduino MCU then the circuit type will default to <code>circuit_C1 (INPUT)</code> .
<code>switched</code>	<code>true</code>	A value returned by <code>read_switch</code> , <code>read_button_switch</code> & <code>read_toggle_switch</code> functions. Signifies switch has been pressed and switch cycle complete, otherwise <code>!switched</code>
<code>on</code>	<code>true</code>	used for toggle switch status. Off is <code>!on</code>
<code>not_used</code>	<code>true</code>	'not used' indicator – marks if a field in the switch control structure is used or not
<code>bad_params</code>	-2	A value returned by <code>add_switch</code> function - invalid parameters
<code>add_failure</code>	-1	A value returned by <code>add_switch</code> function - could not insert a given switch, i.e. no slots left
<code>link_success</code>	0	A value returned by <code>link_switch_to_output</code> function - output pin successfully linked to a switch
<code>link_failure</code>	-1	A value returned by <code>link_switch_to_output</code> function - output pin could not be linked to a switch
<code>none_switched</code>	255	<code>last_switched_id</code> variable initialised to this value until first switch is actuated

Other Declarations

The library supports a useful variable, accessible to the end user developer, that records the id of the switch that has last been actuated, i.e. switched. This variable is declared and initialised as follows:

```
uint8_t last_switched_id = none_switched;
```

And may be referenced as follows (example):

```
my_switches.last_switched_id
```

See the example of its use in the Corollary section below.

Specifications - Switch Control Functions

Type	<code>int</code>	Name	<code>add_switch</code>
Parameters	<code>uint8_t sw_type, uint8_t sw_pin, uint8_t circ_type</code> parameter choices are: <code>sw_type</code> - is either ' <code>button_switch</code> ' or ' <code>toggle_switch</code> ', <code>sw_pin</code> - is the digital pin assigned to the switch, <code>circ_type</code> - is either ' <code>circuit_C1/INPUT</code> ', ' <code>circuit_C2/INPUT_PULLUP</code> ' or, ' <code>circuit_C3/PULLDOWN</code> (ESP 32 only)		
Purpose / functionality	This function will add (create) the specified switch (parameters) to the switch control structure, if possible. There are three possible outcomes from an <code>add_switch</code> call: 1. Successful addition of switch. In this case the return value is ≥ 0 and represents the physical slot (location 'switch_id/token') of the switch in the switch control structure. This should be retained by the calling code/design. 2. No further slots available in the switch control structure, all are used. 3. The supplied parameters are 'bad'. The results of an <code>add_switch</code> call are as below.		
Return values	Return values are: ≥ 0 success, switch added to switch control struct(ure) - the switch control structure entry number is returned (switch_id/token) for the switch added, -1 <code>add_failure</code> - no slots available in the switch control structure, -2 <code>bad_params</code> - given parameter(s) for switch are not valid.		

Example

```
void create_my_switches() {
  for (int sw = 0; sw < num_switches; sw++) {
    int switch_id =
      my_switches.add_switch(my_switch_data[sw][0], // switch type
                           my_switch_data[sw][1], // digital pin number
                           my_switch_data[sw][2]); // circuit type

    if (switch_id < 0)
    { // There is a data compatibility mismatch (-2),
      // or no room left to add switch (-1).
      Serial.print("Failure to add a switch:\nswitch entry:");
      Serial.print(switch_id);
      Serial.print(", data line = ");
      Serial.print(my_switch_data[sw][0]);
      Serial.print(", ");
      Serial.print(my_switch_data[sw][1]);
      Serial.print(", ");
      Serial.println(my_switch_data[sw][2]);
      Serial.println("!!! PROGRAMME TERMINATED !!!");
      Serial.flush();
      exit(1);
    } else {
      // 'switch_id' is the switch control slot entry for this switch (sw),
      // so we can use this, if required, to know where our switches are
      // in the control structure by keeping a note of them against their
      // my_switch_data config settings.
      my_switch_data[sw][3] = switch_id;
    }
  }
} // End create_my_switches
```


Type	<code>int</code> Name <code>link_switch_to_output</code>
Parameters	<code>uint8_t</code> switch_id, <code>uint8_t</code> output_pin, <code>bool</code> HorL
Purpose / functionality	<p>This function will link the given digital pin (output_pin) to an already created/defined switch (switch_id) and initialise it according to the specified parameter, as follows:</p> <p><code>pinMode</code>(output_pin, HorL), where HorL is either <code>LOW</code> or <code>HIGH</code></p> <p>Once linked, the output pin will be flipped between <code>LOW/HIGH</code> or <code>HIGH/LOW</code> each time the associated switch is read (tested) by the <code>read_switch</code> function and found to have been actuated (switched).</p> <p>Note that:</p> <ol style="list-style-type: none"> 1. This feature allows simple digital output pin switching without any requirement for end user coding. 2. The output can be initialised at either <code>LOW</code> or <code>HIGH</code> level. 3. Automatic output pin flipping only occurs via use of the <code>read_switch</code> function only. If switches have a linked output and they need to be read <u>without</u> automatic output pin flipping then use <code>read_button_switch</code> / <code>read_toggle_switch</code>, instead. These two functions will not 'flip' associated switch output levels. 4. <u>Redefining a linked switch output</u> - existing defined switch linked outputs can be redefined, as required, by further calls to the switch link function. 5. <u>Removing a linked switch output</u> - if a switch has a linked output defined and it is necessary to remove it then this can be done by a call to <code>link_switch_to_output</code> with an output pin value of 0. The output level will be set according to the HorL parameter. For example: <pre>link_result = my_switches.link_switch_to_output(switch_id, 0, LOW); // set output level to low</pre> <p>However, if the output level is to remain unaltered then set the HorL parameter to 'my_switches.<code>switches</code>[switch_id].<code>switch_out_pin_status</code>',</p> <p>where 'my_switches' is the name of your class for the Switches class.</p> <p>For example:</p> <pre>link_result = my_switches.link_switch_to_output(switch_id, 0, my_switches.switches[switch_id]. switch_out_pin_status); //don't change</pre>
Return values	<p>0, <code>link_success</code> – linking was successful</p> <p>-1, <code>link_failure</code> – linking failed, switch_id not in range of defined switches</p>
Example	
<p>Example 1:</p> <pre>// Link/associate this switch to the in-built led (normally pin 13) // with the switch we have just installed/created so that every // time the switch is actuated the built in LED will be automatically // flipped. Start with LED at LOW setting. int link_result = my_switches.link_switch_to_output(switch_id,</pre>	

Type	int	Name	add_switch
<pre> LED_BUILTIN, LOW); if (link_result == link_failure) { // linking failed, invalid switch id Serial.begin(9600); Serial.println(F("Failure to link an output to a switch")); Serial.println(F("!!PROGRAM TERMINATED!!")); Serial.flush(); exit(2); } Example 2: // Link/associate this switch to the relay output pin // with the switch we have just installed/created so that every // time the switch is actuated the relay will be automatically // flipped. Start with relay at HIGH setting. int link_result = my_switches.link_switch_to_output(switch_id, relay_1, HIGH); if (link_result == link_failure) { // linking failed, invalid switch id Serial.begin(9600); Serial.println(F("Failure to link an output to a switch")); Serial.println(F("!!PROGRAM TERMINATED!!")); Serial.flush(); exit(2); } </pre>			

Type	int	Name	num_free_switch_slots
Parameters	none		
Purpose / functionality	Returns the number of free slots available in the switch control structure.		
Return values	0 - maximum number of switches defined		
Example			
<pre>Serial.print("\nNumber of free switch slots in the SCS = "); Serial.println(my_switches.num_free_switch_slots());</pre>			

Type	bool	Name	read_switch
Parameters	uint8_t switch_id		
Purpose / functionality	<p>Function will read the given switch returning a result as below.</p> <p>Note that:</p> <ol style="list-style-type: none">1. The switch_id parameter is the switch entry number in the switch control structure of the switch to be read. This is the returned value from the add_switch function call.2. If an invalid switch_id is given the read function exits with a return value of !switched.3. If a switch has a linked output pin associated with it then this function will 'flip' the current output pin level, i.e. from LOW to HIGH, or from HIGH to LOW. <p>See add_switch and link_switch_to_pin for further information.</p>		
Return values	switched or !switched		
Example			

Type	bool	Name	read_switch
Example 1: <pre>// the switch does not have an output pin linked to it, so we // need to handle the flipping of the LED do { if (my_switches.read_switch(switch_id) == switched) { led_level = HIGH - led_level; // flip between HIGH and LOW each cycle digitalWrite(LED_BUILTIN, led_level); } } while (true);</pre> Example 2: <pre>// the switch has been defined with a linked/associated output pin // connected to a LED. // We therefore have nothing to do but keep reading the switch and the // LED will be automatically flipped for us. do { my_switches.read_switch(switch_id); } while (true);</pre>			

Type	bool	Name	read_button_switch
Parameters	uint8_t switch_id		
Purpose / functionality	<p>This is used by the read_switch function and deals specifically with reading momentary button style switches.</p> <p>The function can be used by end user code, but note:</p> <ol style="list-style-type: none">1. Remember that the switch_id parameter is the switch entry number in the switch control structure of the switch to be read.2. If the switch has a linked/associated output pin then it will <u>not</u> be processed.		
Return values	switched or !switched		
Example			
<pre>if (my_switches.read_button_switch(switch_id) == switched) { // button switch pressed ... }</pre>			

Type	bool	Name	read_toggle_switch
Parameters	uint8_t switch_id		
Purpose / functionality	<p>This is used by the read_switch function and deals specifically with reading toggle style switches.</p> <p>The function can be used by end user code, but note:</p> <ol style="list-style-type: none">1. Remember that the switch_id parameter is the switch entry number in the switch control structure of the switch to be read.2. If the switch has a linked/associated output pin then it will <u>not</u> be processed.		
Return values	switched or !switched		
Example			
<pre>if (my_switches.read_toggle_switch(switch_id) == switched) { // toggle switch switched ... }</pre>			

Type	<code>void</code>	Name	<code>reset_switch</code>
Parameters	<code>uint8_t switch_id</code>		
Purpose / functionality	This function will reset the given switch to a inactive state, i.e. not in transition. If the given switch is not in transition then it will have no material effect. It is a useful function if, for example, code returns to an active state following deep sleep, or from interrupts. Of course, its use depends entire on the design of a sketch or application.		
Return values	None		
Example			
<pre>// // Interrupt handler for the deep sleep interrupt pin. // void rise_and_shine() { // Remove the interrupt handler to prevent any spurious interrupts, // the handler will be re-established when ready for sleep detachInterrupt(digitalPinToInterrupt(wake_up_switch)); // reset the options switch which may have been pending at time deep sleep time out my_switches.reset_switch(options_switch_id); }</pre>			

Type	<code>void</code>	Name	<code>reset_switches</code>
Parameters	<code>uint8_t</code> switch_id		
Purpose / functionality	This function will reset ALL declared switches to a inactive state, i.e. not in transition. If any switch is not in transition then it will have no material effect. It is a useful function if, for example, code returns to an active state following deep sleep, or from interrupts. Of course, its use depends entire on the design of a sketch or application.		
Return values	None		
Example			
<pre>// // Interrupt handler for the deep sleep interrupt pin. // void rise_and_shine() { // Remove the interrupt handler to prevent any spurious interrupts, // the handler will be re-established when ready for sleep detachInterrupt(digitalPinToInterrupt(wake_up_switch)); // reset any switches that may have been pending/in transition at time of a manual // deep sleep request my_switches.reset_switches(); }</pre>			

Type	<code>bool</code> Name <code>button_is_pressed</code>
Parameters	<code>uint8_t</code> switch id
Purpose / functionality	<p><i>Note: this function is only relevant for button switches, i.e. momentary switches. It is <u>not</u> relevant for use with toggle switches.</i></p> <p>This function will return one of two conditions – <code>true</code> or <code>false</code>. If the specified button switch is in transition (i.e. it is being pressed and not yet fully switched) then the value returned will be <code>true</code>, otherwise the value return will be <code>false</code>.</p> <p>Note:</p> <ul style="list-style-type: none"> • The function is <u>ONLY</u> relevant for switches that are declared as type <code>BUTTON</code> • If used with a none button switch the function will return <code>false</code> • If the button switch has a linked output pin defined then this function <u>WILL NOT</u> automatically switch (toggle) the linked output. If this is required use the overloaded variant of this function with a second parameter of <code>true</code> • This function is equivalent to its overload variant with the following parameters: <code>button_is_pressed(sw_id, false)</code> ;
Return values	<p><code>true</code> - the specified switch is in transition, i.e. being pressed</p> <p><code>false</code> - the specified switch is NOT in transition, i.e. it is quiescent and NOT being pressed</p>

Example

Example 1:

This example will read the specified switch continually and will action the code under the scope of the while statement whenever the switch is pressed. Note that when the switch is released it will have a status of 'not pending' or 'not in transition'. This is an important point to understand as this is not always the case with compounded if/while logic – see example 2 below.

```
void loop() {
  int count;
  do {
    count = 0; //reset for new cycle
    while (my_switches.button_is_pressed(sw_1_id))
    {
      // whilst the switch is being pressed perform tasks
      count++;
      Serial.print("count = ");
      Serial.println(count);
      Serial.flush();
      delay(500); // wait for ½ second before retesting the switch
    }
  } while (true);
}
```

Example 2:

This example will read two specified switches continually and will action the code under the scope of the while statement whenever BOTH switches are pressed. To note is that one of the two button test functions will be the cause of terminating the while logic conditions, i.e. one switch will be released before the other and b so detected. In this case we have the scenario that one switch will have a status of not in transition and the other still in transition. This may cause some issues with further code and, to remedy this, the following example includes two statements outside of the while loop to force a reset of each of the two switches. This same logic will apply if more than two switches appear as a part of compounded conditional logic.

```
void loop() {
  int count;
  do {
    count = 0; //reset for new cycle
    while (my_switches.button_is_pressed(sw_1_id) &&
           my_switches.button_is_pressed(sw_2_id))
```

Type	bool	Name	button_is_pressed
<pre> { // whilst BOTH switches are being pressed perform tasks count++; Serial.print("count = "); Serial.println(count); Serial.flush(); delay(500); // wait for ½ second before retesting the switch } // either switch may have terminated the while logic, so ensure // both switches are reset as not pending/not in transition my_switches.reset_switch(sw_1_id); my_switches.reset_switch(sw_2_id); } while (true); } </pre>			

Type	bool	Name	button_is_pressed
Parameters	unit8_t switch_id, bool process_link		
Purpose / functionality	<p><i>Note: this function is only relevant for button switches, i.e. momentary switches. It is <u>not</u> relevant for use with toggle switches.</i></p> <p>This function may be used if the specified button switch has a linked output which is required to be automatically switched (i.e. toggled) upon completion of the switching cycle (i.e. the button switch has been released).</p> <p>The function will return one of two conditions – <code>true</code> or <code>false</code>. If the specified button switch is in transition (i.e. it is being pressed and not yet fully switched) then the value returned will be <code>true</code>, otherwise the value return will be <code>false</code>.</p> <p>Note:</p> <ul style="list-style-type: none"> The function is <u>ONLY</u> relevant for switches that are declared as type <code>BUTTON</code> If used with a none button switch the function will return <code>false</code> and any linked output switching ignored Any linked output may be automatically switched if a request to do so is provided via the second parameter – i.e. by specifying 'process_link' as <code>true</code>. If the second parameter is specified as <code>false</code> then any linked output <u>WILL NOT</u> be automatically switched WARNING – if this function is used in a compounded logic test then switches with linked outputs may NOT be automatically switched (i.e. toggled). Consider the following two switches, each of which has a linked output: <pre> while (my_switches.button_is_pressed(sw_1_id, true)&& my_switches.button_is_pressed(sw_2_id, true)){ // both switches are simultaneously being pressed // so process... } my_switches.reset_switches();//reset all switches to inactive </pre> <p>Processing of the while loop continues as long as <u>both</u> switches are simultaneous being pressed. But, at some point, one or other switch will be detected as being released and its linked output will be automatically processed. However, the other switch will not have had the benefit of being allowed to complete its switching cycle even though it has been</p>		

Type	bool	Name	button_is_pressed
	released because of the compounded logic test under the while statement. Its linked output will <u>not</u> therefore be automatically switched. So do be aware of the use of this function in compounded constructs.		
Return values	true - the specified switch is in transition, i.e. being pressed false - the specified switch is NOT in transition, i.e. it is quiescent and NOT being pressed		
Example			
Example 1:			
<pre>// test and process switch 1, with linked output while(button_is_pressed(sw_1_id, true)){ // switch 1 is being pressed so process. // Its linked output (LED) will be automatically // toggled on button release ... }</pre>			
Example 2:			
<pre>// test and process switch 1, which has a linked // output, but we do not want it to be automatically // processed on switch release while(button_is_pressed(sw_1_id, false)){ // switch 1 is being pressed so process. ... }</pre>			
Example 3, alternative to Example 2:			
<pre>// test and process switch 1, which has a linked // output, but we do not want it to be automatically // processed on switch release while(button_is_pressed(sw_1_id)){ // switch 1 is being pressed so process. ... }</pre>			

Type	<code>void</code>	Name	<code>print_switch</code>
Parameters	<code>uint8_t switch_id</code>		
Purpose / functionality	<p>The function prints the switch parameters of the switch defined at slot <code>switch_id</code> in the switch control structure to the serial monitor.</p> <p>It can be helpful in the debugging phase and removed thereafter.</p>		
Return values	none		
Example			
<pre>my_switches.print_switch(3);</pre> <p>Example output a toggle switch, configured as <code>circuit_C1</code> and occupying entry 3 (<code>switch_id = 3</code>) in the switch control structure:</p> <pre>sw_id: = 3 sw_type = TOGGLE SWITCH sw_pin = 5 circ_type = INPUT/circuit_C1/0 on_value = HIGH sw_status = OFF pending = NO db_start = 0 msec Linked output pin = 8 linked pin status = LOW</pre>			

Type	void	Name	print_switches
Parameters	none		
Purpose / functionality	The function prints the switch parameters of ALL switches held in the switch control structure to the serial monitor. It can be helpful in the debugging phase and removed thereafter.		
Return values	none		
Example			
<pre>my_switches.print_switches();</pre> <p>Example output for 6 defined switches - 3 x button & 3 x toggle, configured as either circuit_C1 or circuit_C2 and with two switches with linked outputs:</p> <p>Declared & configured switches:</p> <pre>sw_id: = 0 sw_type = BUTTON SWITCH sw_pin = 2 circ_type = INPUT_PULLUP/circuit_C2/2 on_value = LOW sw_status = n/a pending = NO db_start = 0 msecs Linked output pin = 13 linked pin status = HIGH</pre> <pre>sw_id: = 1 sw_type = BUTTON SWITCH sw_pin = 3 circ_type = INPUT_PULLUP/circuit_C2/2 on_value = LOW sw_status = n/a pending = NO db_start = 0 msecs *** No linked output pin</pre> <pre>sw_id: = 2 sw_type = BUTTON SWITCH sw_pin = 4 circ_type = INPUT/circuit_C1/0 on_value = HIGH sw_status = n/a pending = NO db_start = 0 msecs *** No linked output pin</pre> <pre>sw_id: = 3 sw_type = TOGGLE SWITCH sw_pin = 5 circ_type = INPUT/circuit_C1/0 on_value = HIGH sw_status = OFF pending = NO db_start = 0 msecs Linked output pin = 8linked pin status = LOW</pre> <pre>sw_id: = 4 sw_type = TOGGLE SWITCH sw_pin = 6 circ_type = INPUT_PULLUP/circuit_C2/2 on_value = LOW sw_status = OFF pending = NO db_start = 0 msecs *** No linked output pin</pre> <pre>sw_id: = 5 sw_type = TOGGLE SWITCH sw_pin = 7 circ_type = INPUT/circuit_C1/0 on_value = HIGH sw_status = OFF pending = NO db_start = 0 msecs *** No linked output pin</pre>			

Type	<code>void</code>	Name	<code>set_debounce</code>
Parameters	<code>uint16_t</code> period		
Purpose / functionality	<p>The function may be used to set the debounce period, in milliseconds, for switch reading functions.</p> <p>Note that:</p> <ol style="list-style-type: none">1. the debounce value is set to 10 milliseconds, by default2. the debounce setting is global and applies to ALL defined switches3. the parameter value must be ≥ 0. Negative values are ignored.		
Return values	none		
Example			
<pre>my_switches.set_debounce(20); // set debounce for 20 msecs</pre>			

Example Sketches

What follows are a number of examples in the use of the `<ez_switch_lib>` library. These are provided to aid understanding in how the `<ez_switch_lib>` can be applied to your projects.

Each example sketch may be copied and pasted directly into the Arduino IDE from the github links provided for each example sketch, compiled and uploaded without any further coding – just ensure that you have downloaded the `<ez_switch_lib>` library files first.

Any additional components beyond an Arduino microcontroller, connecting wires and a breadboard are indicated for each sketch.

The example sketches are:

1. Example 1.1 - turning on and off the in-built LED of the Arduino microcontroller (normally on pin 13) using a button switch using direct coding.
2. Example 1.2 – as for example 1.1 but using the function `link_switch_to_output` to flip the in-built LED using indirect coding.
3. Example 2.1 - turning on and off the in-built LED of the Arduino microcontroller (normally on pin 13) using a toggle switch using direct coding.
4. Example 2.2 – as for example 2.1 but using the function `link_switch_to_output` to flip the in-built LED using indirect coding.
5. Example 3.1 - four switches, two button and two toggle, wired in different schemes, with each switch turning on and off an associated LED using direct coding.
6. Example 3.2 - as for example 3.1 but using the function `link_switch_to_output` to flip each of the associated LEDs using indirect coding.
7. Example 4 - six switches, three button and three toggle, wired in different schemes, with each switch being processed by its own switch-case statement. The sketch incorporates a mix of direct coding and use of the function `link_switch_to_output` to control the effects of the switches, using the serial monitor, LEDs and relays.
8. Example 5 – one toggle switch and two button switches used to provide time adjustment capability for hours and minutes (24 hour clock). This example demonstrates the use of the library's internal switch control struct(ure) variables and settings directly to achieve the required functionality.

All of the sketches can be accessed from github - follow the specific github link with each example. Alternatively, the main `<ez_switch_lib>` github page with the `<ez_switch_lib>` files (.h, .cpp, .txt and .pdf files) can be found at this [link](#).


Example 1.1 - Turning LED On/Off With a Button Switch, Directly Coded

This example sketch uses a button switch and will turn the Arduino in-built led on and off with each press. The switch is wired for `circuit_C1`.

Note that a led state change will only occur when the button switch is released, that is after the completion of the switching cycle.

The switch mappings and outputs are:

Project Name:		Example 1.1 – button switch, no linking					Date:	4 March 2021
Switch Configs					Linked Outputs		Notes	
Pin	Switch Type		Circuit Type		Pin	Initial Value		
	Button	Toggle	C1	C2		LOW	HIGH	
2	X		X					No linked output, button will flip in-built LED by direct coding

Components required	Circuit schemes
1 x button switch	 <p style="text-align: center;">circuit_C1</p> <p style="text-align: center;">Figure 1 – Circuit C1</p>

The sketch can be also accessed from github, [here](#).

```

/*
  Ron D Bentley, Stafford, UK
  Mar 2021

  %%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%
  -      Example of use of the ez_switch_lib library      -
  Example 1.1
  Reading single button switch to turn built in led on/off.
  When the button switch is actuated, the in-built led
  (LED_BUILTIN), will be flipped ON/OFF etc by using suitable
  coding in the sketch's main loop.
  %%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%

  This example and code is in the public domain and
  may be used without restriction and without warranty.

  */
#include <Arduino.h>
#include <ez_switch_lib.h> // ez_switch_lib .h & .cpp files are stored under
...\\Arduino\\libraries\\ez_switch_lib\\

int  switch_id;
bool led_level = LOW;    // start with led off

#define num_switches 1  // only a single switch in this sketch example

// Declare/define the switch instance of given size
Switches my_switches(num_switches);

void setup() {
  // Attach a button switch to digital pin 2, with
  // an external pull down resistor, circuit_C1,
  // and store the switch's id for later use.
  switch_id = my_switches.add_switch(
    button_switch,
    2,

```

```
        circuit_C1);
// validate the return
if (switch_id < 0) {
    // Error returned - there is a data compatibility mismatch (-2, bad_params),
    // or no room left to add switch (-1, add_failure).
    Serial.begin(9600);
    Serial.println(F("Failure to add a switch"));
    if (switch_id == add_failure) {
        Serial.println(F("add_switch - no room to create given switch"));
    } else {
        // Can only be that data for switch is invalid
        Serial.println(F("add_switch - one or more parameters is/are invalid"));
    }
    Serial.println(F("!!PROGRAM TERMINATED!!"));
    Serial.flush();
    exit(1);
}
// Initialise built in led and turn to off
pinMode(LED_BUILTIN, OUTPUT);
digitalWrite(LED_BUILTIN, LOW);
}

void loop() {
    // Keep reading the switch we have created and toggle the built in
    // led on/off for each press.
    do {
        if (my_switches.read_switch(switch_id) == switched) {
            // Flip between HIGH and LOW each cycle
            led_level = HIGH - led_level;
            digitalWrite(LED_BUILTIN, led_level);
        }
    } while (true);
}
```


Example 1.2 - Turning LED On/Off With a Button Switch, Indirectly Coded

This example sketch uses a button switch to turn the Arduino in-built led on and off with each press, indirectly, by using the `link_switch_to_output` function. Compare this sketch with example 1.1 sketch and note the differences – the button switch is linked to an output pin and no code exists in the sketch to flip the output pin (in-built LED). The switch is wired for `circuit_C1`.

Note that a led state change will only occur when the button switch is released, that is after the completion of the switching cycle.

The switch mappings and outputs are:

Project Name:					Example 1.2 – button switch, with linking					Date:		4 March 2021	
Switch Configs					Linked Outputs					Notes			
Pin	Switch Type		Circuit Type		Pin	Initial Value							
	Button	Toggle	C1	C2		LOW	HIGH						
2	X		X		13	X		LED_BUILTIN – <u>no</u> direct coding needed to flip the LED					

Components required	Circuit schemes
1 x button switch	<p><code>circuit_C1</code></p>  <p>Arduino Microcontroller Figure 1 – Circuit C1</p>

The sketch can be accessed from github [here](#).

```

/*
  Ron D Bentley, Stafford, UK
  Mar 2021
  %%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%
  -      Example of use of the ez_switch_lib library      -
  Example 1.2
  Reading single button switch to turn built in led on/off, but
  in this example we shall link the switch to an output pin
  (LED_BUILTIN) using a ez_switch_lib function, so that when
  actuated, the output pin will be automatically flipped
  HIGH-LOW etc each time the button switch is pressed WITHOUT
  any further coding.
  %%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%

  This example and code is in the public domain and
  may be used without restriction and without warranty.

*/
#include <Arduino.h>
#include <ez_switch_lib.h> // ez_switch_lib .h & .cpp files are stored under
...\\Arduino\\libraries\\ez_switch_lib\\

int switch_id;

#define num_switches 1 // only a single switch in this sketch example

// Declare/define the switch instance of given size
Switches my_switches(num_switches);

void setup() {
  // Attach a button switch to digital pin 2, with
  // an external pull down resistor, circuit C1,

```

```
// and store the switch's id for later use.
switch_id = my_switches.add_switch(
    button_switch,
    2,
    circuit_C1);
// validate the return
if (switch_id < 0) {
    // Error returned - there is a data compatibility mismatch (-2, bad_params),
    // or no room left to add switch (-1, add_failure).
    Serial.begin(9600);
    Serial.println(F("Failure to add a switch"));
    if (switch_id == add_failure) {
        Serial.println(F("add_switch - no room to create given switch"));
    } else {
        // can only be that data for switch is invalid
        Serial.println(F("add_switch - one or more parameters is/are invalid"));
    }
    Serial.println(F("!!PROGRAM TERMINATED!!"));
    Serial.flush();
    exit(1);
}

// Link/associate this switch to the in-built led (normally pin 13)
// with the switch we have just installed/created so that every
// time the switch is actuated the built in LED will be automatically
// flipped. Start with LED at low setting.
int link_result = my_switches.link_switch_to_output(
    switch_id,
    LED_BUILTIN,
    LOW);
if (link_result == link_failure) {
    // linking failed, invalid switch id
    Serial.begin(9600);
    Serial.println(F("Failure to link an output to a switch"));
    Serial.println(F("!!PROGRAM TERMINATED!!"));
    Serial.flush();
    exit(2);
}

void loop() {
    do {
        // just keep reading, LED_BUILTIN will automatically be flipped for us
        // so we dont need to do anything else
        my_switches.read_switch(switch_id);
    }
    while (true);
}
```


Example 2.1 - Turning LED On/Off With a Toggle Switch, Directly Coded

This example sketch uses a toggle switch and will turn the Arduino in-built led on and off with each actuation. The sketch is essentially the same as example 1.1, the difference being that a toggle switch type is declared instead of a button type. The switch is wired for `circuit_C1`.

Note that a led state change occurs at each position of the toggle switch.

The switch mappings and outputs are:

Project Name:		Example 2.1 – toggle switch, no linking					Date:	4 March 2021
Switch Configs					Linked Outputs			Notes
Pin	Switch Type		Circuit Type		Pin	Initial Value		
	Button	Toggle	C1	C2		LOW	HIGH	
2		X	X					No linked output, toggle will flip in-built LED by direct coding

Components required	Circuit schemes
1 x toggle switch	<p><code>circuit_C1</code></p>  <p>Figure 1 – Circuit C1</p>

The sketch can be accessed from github [here](#).

```

/*
  Ron D Bentley, Stafford, UK
  Mar 2021

  %%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%
  -      Example of use of the ez_switch_lib library      -
  Example 2.1
  Reading single toggle switch to turn built in led on/off.
  When the toggle switch is activated, the in-built led
  (LED_BUILTIN), will be flipped ON/OFF etc by using suitable
  coding in the sketch's main loop.
  %%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%

  This example and code is in the public domain and
  may be used without restriction and without warranty.

*/
#include <Arduino.h>
#include <ez_switch_lib.h> // ez_switch_lib .h & .cpp files are stored under
...\\Arduino\\libraries\\ez_switch_lib\\

int  switch_id;
bool led_level = LOW;

#define num_switches 1 // only a single switch in this sketch example

// Declare/define the switch instance of given size
Switches my_switches(num_switches);

void setup() {
  // Attach a toggle switch to digital pin 2, with
  // an external pull down resistor, circuit_C1,
  // and store the switch's id for later use.
  switch_id = my_switches.add_switch(
    toggle switch,

```

```
        2,  
        circuit_C1);  
  
// Validate the return  
if (switch_id < 0) {  
    // Error returned - there is a data compatibility mismatch (-2, bad_params),  
    // or no room left to add switch (-1, add_failure).  
    Serial.begin(9600);  
    Serial.println(F("Failure to add a switch"));  
    if (switch_id == add_failure) {  
        Serial.println(F("add_switch - no room to create given switch"));  
    } else {  
        // Can only be that data for switch is invalid  
        Serial.println(F("add_switch - one or more parameters is/are invalid"));  
    }  
    Serial.println(F("!!PROGRAM TERMINATED!!"));  
    Serial.flush();  
    exit(1);  
}  
  
// Initialise built in led and turn to off  
pinMode(LED_BUILTIN, OUTPUT);  
digitalWrite(LED_BUILTIN, LOW);  
}  
  
void loop() {  
    // keep reading the switch we have created and toggle the built in  
    // led on/off for each press.  
    do {  
        if (my_switches.read_switch(switch_id) == switched) {  
            // flip between HIGH and LOW each cycle  
            led_level = HIGH - led_level;  
            digitalWrite(LED_BUILTIN, led_level);  
        }  
    } while (true);  
}
```


Example 2.2 - Turning LED On/Off With a Toggle Switch, Indirectly Coded

This example sketch uses a toggle switch to turn the Arduino in-built led on and off, indirectly, by using the `link_switch_to_output` function. It is essentially the same sketch as in example 2.1, above. Compare this sketch with example 2.1 sketch and note the differences – the toggle switch is linked to an output pin and no code exists in the sketch to flip the output pin (in-built LED).

Note that a led state change occurs at each position of the toggle switch.

The switch mappings and outputs are:

Project Name:			Example 2.2 – toggle switch, with linking					Date:	4 March 2021
Switch Configs					Linked Outputs			Notes	
Pin	Switch Type		Circuit Type		Pin	Initial Value			
	Button	Toggle	C1	C2		LOW	HIGH		
2		X	X		13		X	LED_BUILTIN – <u>no</u> direct coding needed to flip the LED	

Components required	Circuit schemes
1 x toggle switch	<p>circuit_C1</p>  <p>Arduino Microcontroller Figure 1 – Circuit C1</p>

The sketch can be accessed from github [here](#).

```

/*
  Ron D Bentley, Stafford, UK
  Mar 2021

  %%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%
  -      Example of use of the ez_switch_lib library          -
  Example 2.2
  Reading single toggle switch to turn built in led on/off.
  Toggle switch is associated with an output pin (LED_BUILTIN)
  using a ez_switch_lib function, so that when activated, the
  output pin will be automatically flipped, HIGH-LOW etc  each
  time the toggle switch is actuated WITHOUT any further coding.
  %%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%

  This example and code is in the public domain and
  may be used without restriction and without warranty.

  */
#include <Arduino.h>
#include <ez_switch_lib.h>  // ez_switch_lib .h & .cpp files are stored under
...\\Arduino\\libraries\\ez_switch_lib\\

int  switch_id;

#define num_switches 1  // only a single switch in this sketch example

// Declare/define the switch instance of given size
Switches my_switches(num_switches);

void setup() {
  // Attach a toggle switch to digital pin 2, with
  // an external pull down resistor, circuit_C1,
  // and store the switch's id for later use.

```



```
switch_id = my_switches.add_switch(  
    toggle_switch,  
    2,  
    circuit_C1);  
// Validate the return  
if (switch_id < 0) {  
    // Error returned - there is a data compatibility mismatch (-2, bad_params),  
    // or no room left to add switch (-1, add_failure).  
    Serial.begin(9600);  
    Serial.println(F("Failure to add a switch"));  
    if (switch_id == add_failure) {  
        Serial.println(F("add_switch - no room to create given switch"));  
    } else {  
        // Can only be that data for switch is invalid  
        Serial.println(F("add_switch - one or more parameters is/are invalid"));  
    }  
    Serial.println(F("!!PROGRAM TERMINATED!!"));  
    Serial.flush();  
    exit(1);  
}  
  
// Link/associate the LED_BUILTIN digital pin (normally pin 13)  
// with the switch we have just installed/created  
// so that every time the switch is activated the built in  
// LED will be automatically be flipped. Start with LED at HIGH setting.  
int link_result = my_switches.link_switch_to_output(  
    switch_id,  
    LED_BUILTIN,  
    HIGH);  
if (link_result == link_failure) {  
    // Linking failed, invalid switch id  
    Serial.begin(9600);  
    Serial.println(F("Failure to link an output to a switch"));  
    Serial.println(F("!!PROGRAM TERMINATED!!"));  
    Serial.flush();  
    exit(2);  
}  
}  
  
void loop() {  
    do {  
        if (my_switches.read_switch(switch_id) == switched) {  
            // just keep reading, LED_BUILTIN will automatically be flipped for us  
            // so we dont need to do anything else  
        }  
    } while (true);  
}
```





Example 3.1 - Turning Multiple LEDs On/Off With Multiple Button & Toggle Switches, Directly Coded


In this example we build on previous examples and see how we can implement and manage a number of button and toggle switches with ease by defining our switch and associated switching output (LED) parameters in an orderly way – we shall use a struct(ure) data type to keep everything we need together.

For the purposes of this example we shall connect two button and two toggle switches, each connected with each type of circuit.

The switch mappings and outputs are:

Project Name:		3.1 mixed switches, no linking						Date:	4 March 2021
Switch Configs					Linked Outputs			Notes	
Pin	Switch Type		Circuit Type		Pin	Initial Value			
	Button	Toggle	C1	C2		LOW	HIGH		
2	X		X					No linked output, button will flip in-built LED by direct coding	
3	X			X				No linked output, button will flip in-built LED by direct coding	
4		X	X					No linked output, toggle will flip in-built LED by direct coding	
5		X		X				No linked output, toggle will flip in-built LED by direct coding	

Components required	Circuit schemes
1 x button switch	<p>circuit_C1</p>  <p>Arduino Microcontroller Figure 1 – Circuit C1</p>
1 x button switch	<p>circuit_C2</p>  <p>Arduino Microcontroller Figure 2 – Circuit C2</p>
1 x toggle switch	<p>circuit_C1</p>  <p>Arduino Microcontroller Figure 1 – Circuit C1</p>
1 x toggle switch	<p>circuit_C2</p>  <p>Arduino Microcontroller Figure 2 – Circuit C2</p>
2 x 10k ohm resistors	<p>1 each for each circuit_C1</p> <p>Standard wiring scheme for connected LED</p>
4 x LEDs	
4 x 220 ohm resistors	

Components required	Circuit schemes
	

The sketch can be accessed from github [here](#).

```

/*
  Ron D Bentley, Stafford, UK
  Mar 2021

  %%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%
  -      Example of use of the ez_switch_lib library      -
  Example 3.1
  Reading multiple button & toggle switches wired with
  different circuit types with each switch turning associated
  leds on/off.
  This example uses a struct(ure) data type to define the
  switch and led data.
  %%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%

  This example and code is in the public domain and
  may be used without restriction and without warranty.

*/
#include <Arduino.h>
#include <ez_switch_lib.h> // ez_switch_lib .h & .cpp files are stored under
...\\Arduino\\libraries\\ez_switch_lib\\

#define not_configured      255 // used to indicate if a switch_control data entry
has be configured

#define num_switches 4

// We will use a struct(ure) data type to keep our switch/LED
// data tidy and readily accessible
struct switch_control {      // struct member meanings:
  uint8_t  sw_type;          // type of switch connected
  uint8_t  sw_pin;           // digital input pin assigned to the switch
  uint8_t  sw_circuit_type;  // the type of circuit wired to the switch
  uint8_t  sw_id;            // holds the switch id given by the add.switch
function for this switch
  uint8_t  sw_led_pin;       // digital pin connecting the LED for this switch
  bool     sw_led_status;    // current status LOW/HIGH of the LED connected to this
switch
} btl[num_switches] = {      // 'btl' = buttons, toggles & LEDs

  //.....switch data.....> <led data, initial setting level>
  button_switch, 2, circuit_C1, not_configured, 8,  HIGH,
  button_switch, 3, circuit_C2, not_configured, 9,  LOW,
  toggle_switch, 4, circuit_C1, not_configured, 10, HIGH,
  toggle_switch, 5, circuit_C2, not_configured, 11,  LOW
};

// Declare/define the switch instance of given size
Switches my_switches(num_switches);

void setup() {
  // Attach each switch to its defined digital pin/circuit type
  // and store the switch's id back in its struct entry for later use.
  for (uint8_t sw = 0; sw < num_switches; sw++) {
    int switch_id = my_switches.add_switch(
      btl[sw].sw_type,
      btl[sw].sw_pin,
      btl[sw].sw_circuit_type);
    // Validate the return
  }
}

```

```
if (switch_id < 0) {
    // Error returned - there is a data compatibility mismatch (-2, bad_params),
    // or no room left to add switch (-1, add_failure).
    Serial.begin(9600);
    Serial.println(F("Failure to add a switch"));
    if (switch_id == add_failure) {
        Serial.println(F("add_switch - no room to create given switch"));
    } else {
        // Can only be that data for switch is invalid
        Serial.println(F("add_switch - one or more parameters is/are invalid"));
    }
    Serial.println(F("!!PROGRAM TERMINATED!!"));
    Serial.flush();
    exit(1);
}
btl[sw].sw_id = switch_id; // store given switch id for this sw for use later

// Now initialise the switch's associated LED and turn on/off according to
preset
pinMode(btl[sw].sw_led_pin, OUTPUT);
digitalWrite(btl[sw].sw_led_pin, btl[sw].sw_led_status);
}
}

void loop() {
    // Keep reading the switches we have created and flip their
    // associated LEDs on/off
    do {
        for (uint8_t sw = 0; sw < num_switches; sw++) {
            if (my_switches.read_switch(btl[sw].sw_id) == switched) {
                // Flip between HIGH and LOW each cycle
                btl[sw].sw_led_status = HIGH - btl[sw].sw_led_status;
                digitalWrite(btl[sw].sw_led_pin, btl[sw].sw_led_status);
            }
        }
    } while (true);
}
```

Example 3.2 - Turning Multiple LEDs On/Off With Multiple Button & Toggle Switches, Indirectly Coded


In this example we build on the previous example 3.1 and see how we can implement and manage a number of button and toggle switches without direct coding for the outputs. In the example sketch we remove the direct coding that deals with the switching of the LED outputs and, instead, we use the function `link_switch_to_output` to associate each switch to an LED output pin. It is essentially the same sketch as in example 3.1, above. Compare this sketch with example 3.1 sketch and note the differences.

For the purposes of this example we shall connect two button and two toggle switches, each connected with each type of circuit.

The switch mappings and outputs are:

Project Name:					3.2 mixed switches, with linking				Date:	4 March 2021	
Switch Configs					Linked Outputs			Notes			
Pin	Switch Type		Circuit Type		Pin	Initial Value					
	Button	Toggle	C1	C2		LOW	HIGH				
2	X		X		8		X	LED to flip – <u>no</u> direct coding needed to flip the LED			
3	X			X	9	X		LED to flip – <u>no</u> direct coding needed to flip the LED			
4		X	X		10		X	LED to flip – <u>no</u> direct coding needed to flip the LED			
5		X		X	11	X		LED to flip – <u>no</u> direct coding needed to flip the LED			

Components required	Circuit schemes
1 x button switch	<p>circuit_C1</p> <p>Arduino Microcontroller Figure 1 – Circuit C1</p>
1 x button switch	<p>circuit_C2</p> <p>Arduino Microcontroller Figure 2 – Circuit C2</p>
1 x toggle switch	<p>circuit_C1</p> <p>Arduino Microcontroller Figure 1 – Circuit C1</p>
1 x toggle switch	<p>circuit_C2</p> <p>Arduino Microcontroller Figure 2 – Circuit C2</p>
2 x 10k ohm resistors	1 each for each circuit_C1
4 x LEDs	Standard wiring scheme for connected LED
4 x 220 ohm resistors	

Components required	Circuit schemes
	

The sketch can be accessed from github [here](#).

```

/*
  Ron D Bentley, Stafford, UK
  Mar 2021

  %%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%
  -      Example of use of the ez_switch_lib library      -
  Example 3.2
  Reading multiple button & toggle switches wired with
  different circuit types with each switch linked to an
  output pin using a ez_switch_lib function, so that when
  activated, the associated switch output pin will be
  automatically flipped, HIGH-LOW etc  each time the switch
  is actuated WITHOUT any further coding.

  To demonstrate, the switch associated outputs are connected
  to leds.
  %%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%

  This example and code is in the public domain and
  may be used without restriction and without warranty.

*/
#include <Arduino.h>
#include <ez_switch_lib.h>  // ez_switch_lib .h & .cpp files are stored under
...\\Arduino\\libraries\\ez_switch_lib\\

#define not_configured      255  // used to indicate if a switch_control data entry
has be configured

#define num_switches 4

// We will use a struct(ure) data type to keep our switch/LED
// data tidy and readily accessible
struct switch_control {      // struct member meanings:
  uint8_t  sw_type;          // type of switch connected
  uint8_t  sw_pin;           // digital input pin assigned to the switch
  uint8_t  sw_circuit_type;  // the type of circuit wired to the switch
  uint8_t  sw_id;            // holds the switch id given by the add.switch
function for this switch
  uint8_t  sw_output_pin;    // digital pin to associate switch to
  bool     sw_output_level;  // define the status level of the defined output pin on
set up
} btl[num_switches] = {      // 'btl' = buttons, toggles & LEDs

  //.....switch data.....>  <output pin initial setting
level>
  button_switch, 2, circuit_C1, not_configured, 8, HIGH,
  button_switch, 3, circuit_C2, not_configured, 9,  LOW,
  toggle_switch, 4, circuit_C1, not_configured, 10, HIGH,
  toggle_switch, 5, circuit_C2, not_configured, 11,  LOW
};

// Declare/define the switch instance of given size
Switches my_switches(num_switches);

void setup() {
  // Attach each switches to its defined digital pin/circuit type
  // and store the switch's id back in its struct entry for later use.
  for (uint8_t sw = 0; sw < num_switches; sw++) {

```

```
int switch_id = my_switches.add_switch(
    btl[sw].sw_type,
    btl[sw].sw_pin,
    btl[sw].sw_circuit_type);
// Validate the return
if (switch_id < 0) {
    // Error returned - there is a data compatibility mismatch (-2, bad_params),
    // or no room left to add switch (-1, add_failure).
    Serial.begin(9600);
    Serial.println(F("Failure to add a switch"));
    if (switch_id == add_failure) {
        Serial.println(F("add_switch - no room to create given switch"));
    } else {
        // Can only be that data for switch is invalid
        Serial.println(F("add_switch - one or more parameters is/are invalid"));
    }
    Serial.println(F("!!PROGRAM TERMINATED!!"));
    Serial.flush();
    exit(1);
}
btl[sw].sw_id = switch_id; // store given switch id for this sw for use later

// Now associate the defined out for this switch so that every time the switch
// is activated the associated output will be automatically be flipped.
// set the output level to whatever is defined in the initialisation data.
int link_result = my_switches.link_switch_to_output(
    switch_id,
    btl[sw].sw_output_pin,
    btl[sw].sw_output_level);
if (link_result == link_failure) {
    // Linking failed, invalid switch id
    Serial.begin(9600);
    Serial.println(F("Failure to link an output to a switch"));
    Serial.println(F("!!PROGRAM TERMINATED!!"));
    Serial.flush();
    exit(2);
}
}
}

void loop() {
    do {
        for (uint8_t sw = 0; sw < num_switches; sw++) {
            if (my_switches.read_switch(btl[sw].sw_id) == switched) {
                // Just keep reading, the read function will automatically
                // flip the associated switch output pins for us so we
                // dont need to do anything else
            }
        }
    } while (true);
}
```

Example 4 – Processing More Button & Toggle Switches

In this example we shall build on the previous examples by implementing six switches – three button and three toggle, to show how we are able to keep adding switches of different wiring schemes. This time we shall incorporate outputs to the serial monitor, LEDs and relays, as follows:

The sketch is configured for 6 switches, 3 x toggle and 3 x button with switches performing the following actions:

- toggle 1 switches a relay, without direct coding, using output linking
- toggle 2 switches a led, without direct coding, using output linking
- toggle 3 also switches a led by direct coding , i.e. not via switch linking
- button 1 produces a switch report using a `<ez_switch_lib>` function
- button 2 switches a relay, without direct coding, using output linking
- button 3 switches a led, without direct coding, using output linking

The mappings for switches and outputs are:

Project Name:		Example 4 - LEDs & Relays						Date:	4 March 2021
Switch Configs					Linked Outputs			Notes	
Pin	Switch Type		Circuit Type		Pin	Initial Value			
	Button	Toggle	C1	C2		LOW	HIGH		
2		X	X		8		X	Relay 1 - <u>no</u> switching coding	
3		X		X	9	X		Led 1 - <u>no</u> switching coding	
4		X	X					Led 3 - needs switching coding	
5	X			X				Output switch report to serial monitor	
6	X		X		10		X	Relay 2 - <u>no</u> switching coding	
7	X			X	11	X		Led 2 - <u>no</u> switching coding	

The switches are polled in succession and processing occurs via a switch-case set of control statements.

We shall also see how we are able to refer to the status of toggle switches outside of them being read by the `read_switch` function and show their status by using a button switch.

To note is that in this example we use a multidimensional array to hold our switch data, rather than a struct(ure) as in example 3.1/3.2 – you decide with approach is best. You will also see that a switch-case series of statements are used to process the switches once triggered.

Make sure to open the serial monitor once the sketch is compiled and uploaded and set to 9600 baud and note the switch circuit schemes are changed from previous set ups, just to further mix things up!

ARDUINO/ESP 32 - Switch Library User Guide

A Library Supporting the Reading of Multiple, Mixed-type Simple Switches & Circuits

Components required	Circuit schemes
2 x button switch	<p>circuit C2</p> <p>Arduino Microcontroller Figure 4 - circuit C2</p>
1 x button switch	<p>circuit C1</p> <p>Arduino Microcontroller Figure 2 - circuit C1</p>
2 x toggle switch	<p>circuit C1</p> <p>Arduino Microcontroller Figure 1 - circuit C1</p>
1 x toggle switch	<p>circuit C2</p> <p>Arduino Microcontroller</p>
3 x 10k ohm resistors	1 each for each circuit C1
3 x LEDs	<p>Standard wiring scheme for connected LED</p>
3 x 220 ohm resistors	
2 x 5v relays	
Serial monitor	9600 baud

The sketch can be accessed from github [here](#).

```

/*
  Ron D Bentley, Stafford, UK
  Mar 2021.

  %%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%
  -           Example of use of the ez_switch_lib library           -
  Example 4
  Reading multiple switches (6) of different types and of mixed wiring
  schemes. Additionally, some switches are linked to a digital
  output such that when they are actuated the linked output level
  is flipped (HIGH->LOW, or LOW->HIGH) automatically without the
  need for any end user coding.

  Switch data in this example is preset in a two dimension array
  and may be varied as appropriate.

  The sketch is configured for 6 switches, 3 toggle and 3 button
  with switches performing the following actions:
  toggle 1 switches a relay, without direct coding, using output linking
  toggle 2 switches a led, without direct coding, using output linking
  toggle 3 also switches a led, but not via switch linking
  button 1 produces a switch report using a ez_switch_lib function
  button 2 switches a relay, without direct coding, using output linking
  button 3 switches a led, without direct coding, using output linking

  The switches are polled in succession and processing occurs
  via a switch-case set of control statements.
  %%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%

  This example and code is in the public domain and
  may be used without restriction and without warranty.

  */
#include <Arduino.h>
#include <ez_switch_lib.h> // ez_switch_lib .h & .cpp files are stored under

```

```
...\Arduino\libraries\ez_switch_lib\  
  
// %%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%  
// Declare/define specific 'my_data' for 'my_project'  
// %%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%  
  
#define num_switches 6  
  
// Switch to Pin Macro Definition List:  
#define my_toggle_pin_1 2 // digital pin number  
#define my_toggle_pin_2 3 // etc  
#define my_toggle_pin_3 4  
  
#define my_button_pin_1 5  
#define my_button_pin_2 6  
#define my_button_pin_3 7  
  
// Digital output pins for linking to switches:  
#define relay_1 8 // output pin for relay 1  
#define relay_2 9 // output pin for relay 2  
#define led_1 10 // output pin for led 1  
#define led_2 11 // output pin for led 2  
#define led_3 12 // output pin for led 3  
  
#define not_configured 255 // used to indicate if the my_switch_data switch output  
pin is to be configured  
  
// Establish type of switch, assigned digital pin and circuit type  
// for each switch we are connecting. Until we present each  
// switch entry to the add.switch function it will not be  
// recorded as configured, hence the use of the final column.  
//  
// Array row definitions are:  
// [sw][0] = switch type, button or toggle  
// [sw][1] = digital input pin for the switch  
// [sw][2] = how the switch is wired/connected  
// [sw][3] = this stores the switch_id returned from add.switch function  
// to be used in all calls to the library's functions where  
// switches are referenced  
// [sw][4] = the digital output pin linked to this switch, if defined  
// [sw][5] = the level the output pin is to be set to at initialisation (linking),  
// if a linked output is configured - must be LOW or HIGH  
//  
// Note that:  
// 'on', 'switched', 'button_switch', 'toggle_switch', 'circuit_C1'  
// and 'circuit_C2' are reserved library defined macros.  
  
uint8_t my_switch_data[num_switches][6] =  
{  
  // <.....switch data.....> <.output pin data.>  
  toggle_switch, my_toggle_pin_1, circuit_C1, 0, relay_1, HIGH, // linked to relay_1  
  toggle_switch, my_toggle_pin_2, circuit_C2, 0, led_1, LOW, // linked to led_1  
  toggle_switch, my_toggle_pin_3, circuit_C1, 0, not_configured, 0, // not linked,  
  flip led_3 by direct code  
  
  button_switch, my_button_pin_1, circuit_C2, 0, not_configured, 0, // not linked,  
  produces switch report  
  button_switch, my_button_pin_2, circuit_C1, 0, relay_2, HIGH, // linked to relay_2  
  button_switch, my_button_pin_3, circuit_C2, 0, led_2, LOW // linked to led_2  
};  
  
// Declare/define the switch instance of given size  
Switches my_switches(num_switches);  
  
//  
// Set up connected switches as per 'my_switch_data' configs  
//  
  
void setup()  
{  
  Serial.begin(9600);
```

```
// Create/install the defined switches...
create_my_switches();

// Set debounce for 20 msecs
my_switches.set_debounce(20);

// initialise the output pin for led_3, as we will deal with
// flipping this led by direct coding
pinMode(led_3, OUTPUT);
digitalWrite(led_3, LOW);
}

void loop()
{
  do {
    // Poll all switches - examine each connected switch in turn and, if switched,
    // process its associated purpose.
    for (int sw = 0; sw < num_switches; sw++) {
      uint8_t switch_id = my_switch_data[sw][3]; // extract the switch id for this
switch, sw
      if (my_switches.read_switch(switch_id) == switched) {
        // This switch ('switch_id') has been pressed, so process via its switch-
case code
        if (my_switches.switches[switch_id].switch_type == button_switch) {
          Serial.print(F("\nbutton switch on digital pin "));
        } else {
          Serial.print(F("\ntoggle switch on digital pin "));
        }
      }
      uint8_t my_switch_pin = my_switches.switches[switch_id].switch_pin;
      Serial.print(my_switch_pin);
      Serial.println(F(" triggered"));
      // Move to switch's associated code section
      switch (my_switch_pin)
      {
        case my_toggle_pin_1:
          // toggle switch 1 triggers a relay (1) which is a linked output
          // so nothing to do here to process the relay
          Serial.print(F("relay 1 switched"));
          break;
        case my_toggle_pin_2:
          // toggle switch 2 flips a led (1) which is a linked output
          // so nothing to do here to process the relay
          Serial.print(F("led 1 switched"));
          break;
        case my_toggle_pin_3:
          // direct coding to flip led_3 following switch actuation (toggle 3)
          static bool led_3_status = LOW; // static because we need to retain
current state between switching
          led_3_status = HIGH - led_3_status; // flip led status
          digitalWrite(led_3, led_3_status);
          Serial.print(F("led 3 switched "));
          break;
        case my_button_pin_1:
          // button switch 1 used to reveal the current status of the switch
control structure
          // members, number of free switch control slots and the on/off status
of all
          // all toggle switches as their status is maintained
          my_switches.print_switches(); // confirm we are set up correctly
          // Report number of free switch slots remaining
          Serial.print(F("\nNumber of free switch slots remaining = "));
          Serial.println(my_switches.num_free_switch_slots());
          // Report on the current status of the toggle switches
          print_toggle_status();
          Serial.flush();
          break;
        case my_button_pin_2:
          // button switch 2 triggers a relay (2) which is a linked output
          // so nothing to do here to process the relay
          Serial.print(F("relay 2 switched"));
          break;
      }
    }
  }
}
```

```
        case my_button_pin_3:
            // button switch 3 flips a led (2) which is a linked output
            // so nothing to do here to process the relay
            Serial.print(F("led 2 switched"));
            break;
        default:
            // Spurious switch index! Should never arise as this is controlled
            // by the for loop within defined upper bound
            break;
    }
    Serial.flush(); // flush out the output buffer
}
}
}
while (true);
}

//
// Print the current status/setting of each toggle switch configured.
// We scan down my_switch_data to pick out toggle switches and if they are
// configured access their status.
//

void print_toggle_status() {
    Serial.println(F("\nToggle switches setting: "));
    for (uint8_t sw = 0; sw < num_switches; sw++) {
        if (my_switch_data[sw][0] == toggle_switch) {
            Serial.print(F("toggle switch on digital pin "));
            Serial.print(my_switch_data[sw][1]);
            Serial.print(F(" is "));
            uint8_t switch_id = my_switch_data[sw][3]; // this is the position in the
switch control struct for this switch
            if (my_switches.switches[switch_id].switch_status == on) {
                Serial.println(F("ON"));
            } else {
                Serial.println(F("OFF"));
            }
        }
    }
}

//
// Create a switch entry for each wired up switch, in accordance
// with 'my' declared switch data.
// add switch params are - switch_type, digital pin number and circuit type.
// Return values from add_switch are:
//   >= 0 the switch control structure entry number ('switch_id') for the switch
//   added,
//   -1 no slots available in the switch control structure,
//   -2 given parameter(s) for switch are not valid.

void create_my_switches() {
    for (int sw = 0; sw < num_switches; sw++) {
        int switch_id =
            my_switches.add_switch(
                my_switch_data[sw][0], // switch type
                my_switch_data[sw][1], // digital pin number
                my_switch_data[sw][2]); // circuit type
        if (switch_id < 0)
        { // There is a data compatibility mismatch (-2, bad_params),
// or no room left to add switch (-1, add failure).
            Serial.print(F("Failure to add a switch:\nSwitch entry:"));
            Serial.print(sw);
            Serial.print(F(", data line = "));
            Serial.print(my_switch_data[sw][0]);
            Serial.print(F(", "));
            Serial.print(my_switch_data[sw][1]);
            Serial.print(F(", "));
            Serial.println(my_switch_data[sw][2]);
            Serial.println(F("!!PROGRAM TERMINATED!!"));
            Serial.flush();
        }
    }
}
```

```
    exit(1);
} else {
    // 'switch_id' is the switch control slot entry for this switch (sw),
    // so we can use this to know where our switches are
    // in the control structure by keeping a note of them in their
    // my_switch_data config settings.
    my_switch_data[sw][3] = switch_id;

    // Now deal with any linked output requirement
    if (my_switch_data[sw][4] != not_configured) {
        // there is an output defined for this switch, so link it
        int link_result =
            my_switches.link_switch_to_output(
                switch_id,           // id of switch to link output to
                my_switch_data[sw][4], // digital output pin number
                my_switch_data[sw][5]); // initial level, HIGH or LOW
        if (link_result == link_failure) {
            // linking failed, invalid switch id
            Serial.println(F("Failure to link an output to a switch"));
            Serial.println(F("!!PROGRAM TERMINATED!!"));
            Serial.flush();
            exit(2);
        }
    }
}
}
}
} // End create_my_switches
```

Example 5 – Using the Libraries Switch Structure Variables

In this final example we see how we can extend the use of switches by accessing their internal control data and develop a sketch that will allow the hours and minutes of an external timer display to be altered independently of each other.




In this sketch we use one toggle switch to ‘activate’ the time change cycle, with a linked output to a LED that will automatically illuminate/extinguish on toggle switching, and two button switches, each allowing hours and minutes to be advanced independently.

The code will also allow the button switches to operate in one of two modes – ‘single-shot’ with each rapid button push advancing the time by +1 (hour or minute) or continuous advance by keeping the button switch pressed.

The external time display is simulated by the sketch with confirmation of <hour:minute> being written to the serial monitor.

The mappings for switches and outputs are:

Project Name:		Example 4 – Timer Adjustment Sketch					Date:	4 March 2021
Switch Configs					Linked Outputs			Notes
Pin	Switch Type		Circuit Type		Pin	Initial Value		
	Button	Toggle	C1	C2		LOW	HIGH	
10		X		X	2	X		Brings adjust code active, LED on when active
11	X			X				Hour adjust button
12	X			X				Minute adjust button

Components required	Circuit schemes
1 x toggle switch	
2 x button switch	
1 x LEDs	<p>Standard wiring scheme for connected LED</p> 
1 x 220 ohm resistors	

The sketch can be accessed from github [here](#).

```
/*
Ron D Bentley, Stafford, UK
Mar 2021

%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%
-           Example of use of the ez_switch_lib library           -
Example 5 - time adjustment sketch
This example shows the use of button and toggle switches to
adjust an external time display.

To implement this successfully we need to use button switches
to adjust hours and minutes individually. We implement this as
follows:

Toggle switch - when on, this will activate the time
adjustment process bringing the two button switches active.
When active,
    1 button switch will advance the hours
    1 button switch will advance minutes.

In this implementation, we wish to advance the times as follows:
    a. if a button is pressed and released immediately, then
       the hour/minute will be advanced by 1, respectively, for
       each press/release
    b. if a button is pressed and kept pressed, then the hour/minute
       will be continually advanced, respectively, automatically
       until it is released.

To accomplish a) and b) we use the standard read_switch function
for the button switches, but we examine their transition
status, as we are not interested in a return of 'switched' or not.
This is an internal flag that is set to true when a button
switch is pressed until the time it is released. The specific
switch flag is 'switches[switch_id].switch_pending'.
This is true when in transition (pending), false otherwise.
By using this flag we are able to utilise the button switches
in either single 'shot mode' or continuous mode for time advancement.

This is an additional feature of the capabilities of the
ez_switch_lib library, and is one that can be used in many
similar applications.

As a final feature, the design links the timer adjust toggle switch
to a LED such that the LED is illuminated when the timer adjust
mode is active, i.e. the toggle switch actuated. This linking is
configured using the ez_switch_lib function 'link_switch_to_output'.
%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%

This example and code is in the public domain and
may be used without restriction and without warranty.

*/
#include <Arduino.h>
#include <ez_switch_lib.h>

#define adjust_led          2  // LED illuminated when adjust switch on
#define hour_adjust_switch  10 // a physical button switch, masquerading as a
toggle switch
#define min_adjust_switch   11 // physical button switch, masquerading as a
toggle switch
#define adjust_switch       12 // actual toggle switch

int hour_id, min_id, adjust_id; // used to record switch ids when declared to
ez_switch_lib

int hour      = 0; // initial hour setting
int min       = 0; // initial minute setting
int now_time  = 0; // to decide if there has been a time adjustment change
int prev_time = 0; // ditto

#define sensitivity 250 // msec - used to provide a short delay between switch
```

```
reading during adjustments

Switches my_switches(3); // only 3 switches to be declared

void setup() {
  Serial.begin(9600);    // we will use the serial monitor to demonstrate
  adjustment process
  // declare the switches we wish to use
  adjust_id = my_switches.add_switch(toggle_switch, adjust_switch, circuit_C2);
  // link adjust switch to LED for auto flipping to show switch is on/off
  my_switches.link_switch_to_output(adjust_id, adjust_led, LOW);

  hour_id = my_switches.add_switch(button_switch, hour_adjust_switch, circuit_C2);
  min_id = my_switches.add_switch(button_switch, min_adjust_switch, circuit_C2);
}
void loop() {
  // keep polling the adjust switch and action if on
  do {
    my_switches.read_switch(adjust_id); // establish switch status
    if (my_switches.switches[adjust_id].switch_status == on) {
      adjust_time(); // adjust switch is on so process any time adjustments
    }
  } while (true);
}

// %%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%
// Adjust the hours and minutes settings whilst
// the time adjust switch is on
// %%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%
void adjust_time() {
  do {
    // While the time adjust switch is set,
    // adjust time according to hour/min switches
    my_switches.read_switch(hour_id);
    if (my_switches.switches[hour_id].switch_pending == true) { // Condition A1
      // hour switch is pressed and in transition
      hour = (hour + 1) % 24;
      now_time = hour * 60 + min; // minutes since 00:00 hours
    }
    my_switches.read_switch(min_id);
    if (my_switches.switches[min_id].switch_pending == true) { // Condition B2
      // minute switch is pressed and in transition
      min = (min + 1) % 60;
      now_time = hour * 60 + min; // minutes since 00:00 hours
    }
    if (now_time != prev_time) {
      // Either hour button or minute button, or both,
      // have been pressed, so update any external display
      // here with hours/mins.
      // In the absence of an external display, we use the
      // serial monitor to show the adjustments
      if (hour < 10) {
        Serial.print("0"); // leading 0
      }
      Serial.print(hour);
      Serial.print(":");
      if (min < 10) {
        Serial.print("0"); // leading 0
      }
      Serial.println(min);
      prev_time = now_time;
      delay(sensitivity); // wait a short time between switch presses
    }
  }
}
```

¹ With version 3.00 of the ez_switch_lib library we have an alternative means of applying the conditional tests at A and B above:

Instead of:	<code>if (my_switches.switches[hour_id].switch_pending == true) {</code>
we can use	<code>if (my_switches.switch_is_pressed(hour_id)) {</code>

and, instead of:	<code>if (my_switches.switches[min_id].switch_pending == true) {</code>
we can use	<code>if (my_switches.switch_is_pressed(min_id)) {</code>

² *ibid.*


```
}  
  my_switches.read_switch(adjust_id); // establish current adjust switch status  
} while (my_switches.switches[adjust_id].switch_status == on ); // keep going  
until deselected  
}
```

Corollary

The <switch_lib> library's functions allow switches of different types, wired in different wiring schemes to be simply read. At their native level they return if a switch has 'switched' or '!switched'. This simple binary result is okay for many applications and uses, however, there are occasions when a little more sophistication and flexibility may be needed. Example 5, above, illustrates how it is possible to make use the library's switch data struct(ure) elements to design advantage; but there are other possibilities!

This section of the User Guide explores some of the deeper <ez_switch_lib> capabilities available to the end user developer.

Switch Mismatching

We add switches into the library's active switch control structure using the `add_switch` function. This allows us to specify a switch type (`button_switch` or `toggle_switch`), the digital pin associated with the switch and how the switch is wired (`circuit_C1` or `circuit_C2`). Ordinarily, we will correctly match the physical switch with the switch type we declare using `add_switch`.

However, if we mismatch the physical switch type with the declared switch type we can use this to our advantage.

Recap the normal operation of both type of switches:

- button switch – it is considered to have been `switched` when it goes through the cycle OFF-ON-OFF. That is, if we press and release the switch we will read one switching event. At rest it will be OFF
- toggle switch – it is considered to have been `switched` when it goes through either OFF-ON or ON-OFF. That is, if we flip the switch up and down we will read two switching events. At rest it will be either OFF or ON.

Buttons as a Toggles

Let's look at using a button switch masquerading as a toggle switch. That is, we physically connect a button switch but declare it using the `add_switch` function as a toggle switch. What is the result?

The switch is initially OFF. We now press it and release it. As far as the library is concerned this is a toggle switch that has just been flipped up and down (i.e. switched to ON and then to OFF). We therefore get two `switched` events, one for the ON event and one for the OFF event. No surprises there.

So, how can this be useful? Well, have a look at the 'Buttons & Lights' game on github ([link](#)). This game uses four button switches each associated/linked to a different coloured LED. The objective of the game is to re-enter a random sequence of lights in the correct order using the button switches.

What we want to achieve is for each button press to illuminate a linked LED for the duration of the press only (i.e. for the LED to be turned on when the button is pressed and turned off when released) and for that button guess to be recorded only after the button's release.

We achieve the game's central requirement by:

1. using simple button switches
2. declaring the button switches as toggle switches using the `add_switch` function. That is, the button switches will be masquerading as toggle switches to our advantage
3. linking each switch to an output pin which has a different coloured LED wired in

The key part of the game, after the switches and associated linkages are made in `setup()` is:

```
1. for (int sw = 0; sw < num_switches; sw++) {
2.   uint8_t sw_id = pseudo_toggles[sw][2]; // switch id given by add_switch
3.   bool sw_status = my_switches.read_switch(sw_id);
4.   if (sw_status == switched &&
5.       my_switches.switches[sw_id].switch_status == !on)
6.   {
7.     // this switch was pressed on and now switched to off and the
8.     // linked output will have been set to LOW (i.e. LED is off),
9.     // so record it - add to guess list
10.    guesses[0]++;
11.    guesses[guesses[0]] = sw; // record this switch's index
12.  }
13. }
```

Line 3 reads the status of the current switch under consideration. Because we have linked our switches to outputs wired with LEDs, these LEDs will automatically turn to on/off when the button switches are pressed/released, respectively, thereby providing a visual confirmation of switch selection – just as we require, but note that we have not explicitly coded this.

Lines 4 and 5 test if the switch has been `switched`, but also that the switch has gone from on to off (`!on`). This is the condition we need to register a single user guess following a complete button press/release cycle. Waiting for the `!on` condition ensures that the switch's linked out LED is turned to off after button switch release. If we tested for just `on`, the LED would not be extinguished.

We can only do this because the switch is declared as a toggle switch and its status is therefore always maintained by the library in the switch control struct(ure) whenever actuated - `switches[sw_id].switch_status`.

We could not have used button switches declared as button switches to readily achieve the above without a degree of additional direct coding, or similarly toggle switches. What the above example demonstrates is that `<ez_switch_lib>` can provide a deeper degree of flexibility and capabilities to the developer.

Many Switches, One Interrupt Service Routine (ISR)

The ability to link a digital output pin to a switch so that it will be automatically flipped on switch actuation can be a useful feature to the end user developer. By way of an academic exercise the sketch below was developed to explore the use of this feature to link multiple switches (of different types and wiring schemes) to a single interrupt service routine or ISR.

Recall that the linking of a switch to an output pin³ for automatic switching/flipping only occurs via use of the switch read function `read_switch`. The other two switch reading functions, `read_button_switch` and `read_toggle_switch`, will not process any linked outputs. This feature provides a degree of flexibility in that there may be circumstances when a switch needs to be read without affecting any linked output.

The sketch does not include very much code but it is extensively documented and the reader should be well versed at this point with the approach adopted. The switch mappings and outputs for this sketch are:

Project Name:		Corollary – Multiple Switches, One ISR						Date:	29 March 2021
Switch Configs					Linked Outputs			Notes	
Pin	Switch Type		Circuit Type		Pin	Initial Value			
	Button	Toggle	C1	C2		LOW	HIGH		
2								Interrupt pin, not physical connected	
3	X		X		2	X		1 st button switch	
4	X		X		2	X		2 nd button switch	
5		X	X		2	X		1 st toggle switch	
6		X		X	2	X		2 nd toggle switch	

The sketch may be accessed from github [here](#).

```
// Ron Bentley, Stafford UK
// March 2021
//
// This example and code is in the public domain and may be used without
// restriction and without warranty.
//
// %%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%
//      Example sketch - Multiple switches handled by a single interrupt
//      %%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%
// This sketch demonstrates how the ez_switch_lib may be used to handle multiple
// switches (button & toggle switches in this example) with a single interrupt
// routine.
//
// The use of the ez_switch_lib library for switches provides:
// * switch type independence
// * switch circuit type independence
// * automatic multiple switch debounce handling
// * parallel switching capabilities, and
// * automatic interrupt handling for all switches
//
// The sketch is designed such that when a toggle switch is switched to the 'on'
// position, or a button switch is pressed AND released a linked output connected
// to a common interrupt pin will cause the associated interrupt handler to be
// fired to process the switch 'on' event.
// NB, and to recap:
// 1. a toggle switch will fire the interrupt when set to 'on'. Setting it back
//    off does not fire the interrupt
// 2. a button switch will ONLY fire the interrupt when pressed 'on' AND
//    then released
//    to off. The interrupt fires on completion of the button switch cycle.
```

³ We use the function `link_switch_to_output` to achieve this capability.

```
//
// Note that:
//   1. error checking on switch set ups has been removed post development.
//   2. the serial monitor is used to confirm the correct operation of the sketch.
//
// The sketch will use digital pin 2 as the common interrupt pin and
// pins 3, 4, 5 and 6 as the switch pins.
//
// For an understanding of the capabilities of the 'ez_switch_lib' library see
// the USER GUIDE:
// https://github.com/ronbentley1/ez_switch_lib-Arduino-
// Library/blob/main/ez_switch_lib_user_guide%2C%20v1.02.pdf
//
// %%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%
#include <ez_switch_lib.h>

int      interrupt_pin = 2; // external interrupt pin

#define num_switches      4
//
// 'my_switches' layout.
// one row of data for each switch to be configured, as follows:
// [[0] = switch type
// [[1] = digital pin connected to switch
// [[2] = the switch_id provided by the add_switch function for the
//       switch declared
// [[3] = the circuit type connecting the switch, here all switches
//       will have 10k ohm pull down resistors wired
uint8_t my_switches[num_switches][4] =
{
  button_switch,  3, 0, circuit_C1,
  button_switch,  4, 0, circuit_C1,
  toggle_switch,  5, 0, circuit_C1,
  toggle_switch,  6, 0, circuit_C1
};

// Create the 'Switches' instance (ms) for the given number of switches
Switches ms(num_switches);

void setup() {
  // Add all switches to library switch control structure
  // and link all to same interrupt pin as a linked output
  for (uint8_t sw = 0; sw < num_switches; sw++) {
    my_switches[sw][2] = ms.add_switch(
      my_switches[sw][0], // switch type
      my_switches[sw][1], // digital pin switch is wired to
      my_switches[sw][3]); // type of circuit switch is wired as
    ms.link_switch_to_output(
      my_switches[sw][2], // switch id
      interrupt_pin,      // digital pin to link to for interrupt
      LOW); // start with interrupt pin LOW, as interrupt will be triggered on RISING
  }
  // Now establish the common interrupt service routine (ISR) that
  // will be used for all declared switches
  attachInterrupt(
    digitalPinToInterrupt(interrupt_pin),
    switch_ISR, // name of the sketch's ISR function to handle switch interrupts
    RISING); // trigger on a rising pin value
  Serial.begin(115200);
} // end of setup function

void loop() {
  // Keep testing switch, and let the interrupt handler do its thing
  // once a switch is switched to 'on'
  for (uint8_t sw = 0; sw < num_switches; sw++) {
    ms.read_switch(my_switches[sw][2]); // my_switches[sw][2] is the switch id
                                         // for switch sw
  }
}
```

```
// %%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%
// ISR for handling interrupt triggers arising from associated switches
// when they transition to on.  The routine knows which switch has generated
// the interrupt because the ez_switch_lib switch read functions record the
// actuated switch in the library variable 'last_switched_id'.
//
// The routine does nothing more than demonstrate the effectiveness of the
// use of a single ISR handling multiple switches by using the serial monitor
// to confirm correct operation.
// %%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%
void switch_ISR()
{
  // Reset the interrupt pin to LOW, so that any other switch will fire the
  // interrupt whilst one or more switches in transition stage
  uint8_t switch_id = ms.last_switched_id; // switch id of switch currently
                                           // switched to on
  digitalWrite(ms.switches[switch_id].switch_out_pin, LOW);
  // For button switches only, reset the linked output pin status to LOW so that
  // it will trigger the interrupt at every press/release cycle.
  if (ms.switches[switch_id].switch_type == button_switch) {
    ms.switches[switch_id].switch_out_pin_status = LOW;
  }
  Serial.print("** Interrupt triggered for switch id ");
  Serial.println(switch_id); // 'this_switch_id' is the id of the triggering switch
  Serial.flush();
} // end of switch_ISR
```

There are other options to be explored.....enjoy!